



Multi-deck terminal block - Modular version - Pitch 10,16mm - 1÷2 poles

GENERAL INFORMATION

pitch:	10,16 mm
housing height:	43,00 mm
housing depth:	34 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	2.8 × 2.8 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	750V
test voltage:	3 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

APPROVALS DATA



EN 60998-1

current:
voltage:

16A
750V



EN 60998-1

16A
750V



UL 1059

16A factory / 15A field
300V

wire section:	2.5mm ²	2.5mm ²	14÷30AWG
torque:	0.5Nm	0.5Nm	4.5Lb-in
FILE:	EP149	40023956	E178356

MATERIALS

housing: PA - UL 94 V0
 screw: Galvanized steel
 clamp/spring: Nickered copper alloy
 terminal: Tin-plated copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVT251-10,16-V	N/A	N/A	N/A
2	MVT252-10,16-V	N/A	N/A	N/A
..	MVT25..-10,16-V	N/A	N/A	N/A