



## Single-deck terminal block - Power - with left flange - Pitch 15mm - 1 pole

### GENERAL INFORMATION

pitch:	15 mm
housing height:	36,30 mm
housing depth:	31 mm
dimensional class:	high
wire section:	35 mm <sup>2</sup> / 2 AWG
clamp opening size:	9 × 8.2 mm
wire stripping:	max 19 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	125A
voltage:	1000V
test voltage:	3.5 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M5
max. torque:	3 Nm / 27 in.lbs

### APPROVALS DATA



current:

-

-

UL 1059  
125A factory / 125A field

voltage:

-

-

600V

wire section:	-	-	1÷20AWG
torque:	-	-	27Lb-in
FILE:	-	-	E178356

### MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickeled copper alloy
terminal:	Tin-plated copper alloy

### AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVP351-15-V-KS	N/A	N/A	N/A
..	MVP35..-15-V-KS	N/A	N/A	N/A