



Male plug-in connector - Stackable version - Pitch 5mm - Poles 02÷24

GENERAL INFORMATION

| | |
|------------------------|----------------|
| pitch: | 5 mm |
| housing height: | 16,50 mm |
| housing depth: | 2.8 mm |
| dimensional class: | slow |
| wire section: | - |
| clamp opening size: | - |
| wire stripping: | - |
| operating temperature: | -40°C ÷ +130°C |

ELECTRICAL CHARACTERISTICS

| | |
|------------------|------|
| current: | 10A |
| voltage: | 250V |
| impulse voltage: | 4 kV |

MECHANICAL CHARACTERISTICS

APPROVALS DATA



| | | | |
|----------|---|---|-------------------------|
| current: | - | - | UL 1059 |
| voltage: | - | - | 18A factory / 15A field |
| FILE: | - | - | 300V |
| | | | E178356 |

MATERIALS

| | |
|---------------|-------------------------|
| housing: | PA - UL 94 V0 |
| screw: | n/a |
| clamp/spring: | n/a |
| terminal: | Tin-plated copper alloy |

AVAILABLE COLOURS

| | |
|-----------------|--------------|
| BK (STD) | |
| other colours: | upon request |

| poles | P/N | pcs/pack | W [Kg]* | W [Kg]* |
|-------|----------|----------|---------|---------|
| 02 | PVST02-5 | N/A | N/A | N/A |
| 03 | PVST03-5 | N/A | N/A | N/A |
| 04 | PVST04-5 | N/A | N/A | N/A |
| 05 | PVST05-5 | N/A | N/A | N/A |

| | | | | |
|----|----------|-----|-----|-----|
| 06 | PVST06-5 | N/A | N/A | N/A |
| 07 | PVST07-5 | N/A | N/A | N/A |
| 08 | PVST08-5 | N/A | N/A | N/A |
| 09 | PVST09-5 | N/A | N/A | N/A |
| 10 | PVST10-5 | N/A | N/A | N/A |
| 11 | PVST11-5 | N/A | N/A | N/A |
| 12 | PVST12-5 | N/A | N/A | N/A |
| 13 | PVST13-5 | N/A | N/A | N/A |
| 14 | PVST14-5 | N/A | N/A | N/A |
| 15 | PVST15-5 | N/A | N/A | N/A |
| 16 | PVST16-5 | N/A | N/A | N/A |
| 17 | PVST17-5 | N/A | N/A | N/A |
| 18 | PVST18-5 | N/A | N/A | N/A |
| 19 | PVST19-5 | N/A | N/A | N/A |
| 20 | PVST20-5 | N/A | N/A | N/A |
| 21 | PVST21-5 | N/A | N/A | N/A |
| 22 | PVST22-5 | N/A | N/A | N/A |
| 23 | PVST23-5 | N/A | N/A | N/A |
| 24 | PVST24-5 | N/A | N/A | N/A |