


Item no.: 750-517
 Product description: 2-CHANNEL RELAY OUTPUT MODULE AC 230 V, DC 300 V
 RELAY 2 CO / POTENTIAL FREE



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Product group	15 (I/O System)
Number of outputs	2 CHANGEOVER CONTACTS (SPDT)
Current consumption max (internal)	90 mA
Switching voltage	AC 250 V / DC 300 V
Switching current (min)	100 mA (12 V DC)
Pull-in time max.	8 ms
Drop-out time max.	4 ms
Printer connection	AgSnO2 gold-plated
Contact material	SILVER ALLOY
Mechanical life	5 x 10 ⁶ SWITCHING OPERATIONS
Electrical life	1 x 10 ⁶ SWITCHING OPERATIONS (AC 1 A/250 V)
Isolation	1.5 kV EFF. (FIELD/SYSTEM), 2.5 kV RATED SURGE VOLTAGE; OVERVOLTAGE CATEGORY III
Internal data width (Bit)	2 Bit
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C
Relative air humidity	95 %

Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27
Degree of protection	IP 20
EMC marine applications - noise proof	gem. Germanischer Lloyd (2003)
EMC marine applications - noise transmission	gem. Germanischer Lloyd (2003)
Conformity marking	CE



Approvals	ATEX
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Weight	52.5 g
Color	light gray
Height	64 mm
Height	2.52 in
Width	12 mm
Width	0.472 in
Depth	100 mm
Depth	3.937 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
750-517	ABS	03-HG374860/3-PDA			
750-517	BSH	Bescheinigung Nr. 467			
750-517	BV	13453/C0 BV			
750-517	DNV	A-12306			
750-517	GL	26 898 - 05 HH			
750-517	KEMA	01 ATEX 1024 X			
750-517	KR	HMB05880-AC002			
750-517	LR	02/20026 (E2)			
750-517	NK	TA06190M			
750-517	PRS	TE/1720/880590/08			
750-517	Rina	ELE153207CS001			
750-517	UL	E175199 Sec.1			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected