

## M8 Assy shielded 4-poles st/st m/m 3,0m



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| Part number        | 21 34 737 3466 030                                                                  |
| Specification      | M8 Assy shielded 4-poles st/st m/m 3,0m                                             |
| HARTING eCatalogue | <a href="https://harting.com/21347373466030">https://harting.com/21347373466030</a> |

### Identification

|               |                              |
|---------------|------------------------------|
| Category      | System cabling               |
| Series        | Circular connectors M8       |
| Element       | Cable assemblies             |
| Specification | Pre-assembled on both sides  |
| Connector 1   | M8 A-coding<br>Male Straight |
| Connector 2   | M8 A-coding<br>Male Straight |
| Type of cable | Copper cable (round)         |

### Version

|                 |                         |
|-----------------|-------------------------|
| Cable length    | 3 m                     |
| Number of cores | 4                       |
| Core structure  | 4x 0.25 mm <sup>2</sup> |
| Shielding       | Shielded                |
| Coding          | A-coding                |

### Technical characteristics

|                      |                |
|----------------------|----------------|
| Limiting temperature | -25 ... +80 °C |
|----------------------|----------------|

### Material properties

|                  |                          |
|------------------|--------------------------|
| Material (cable) | PVC                      |
| Colour (cable)   | Grey                     |
| RoHS             | compliant with exemption |



**Pushing Performance**  
 Since 1945

## Material properties

|                                      |                                                        |
|--------------------------------------|--------------------------------------------------------|
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                           | compliant with exemption                               |
| China RoHS                           | 50                                                     |
| REACH Annex XVII substances          | Not contained                                          |
| REACH ANNEX XIV substances           | Not contained                                          |
| REACH SVHC substances                | Yes                                                    |
| REACH SVHC substances                | Lead                                                   |
| ECHA SCIP number                     | 0d7d3693-d625-47ab-934a-d241bf72c86e                   |
| California Proposition 65 substances | Yes                                                    |
| California Proposition 65 substances | Lead                                                   |

## Commercial data

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Packaging size                 | 1                                            |
| Net weight                     | 1 g                                          |
| Country of origin              | Czechia                                      |
| European customs tariff number | 85444290                                     |
| GTIN                           | 5713140249028                                |
| eCl@ss                         | 27060390 Ready-made data cable (unspecified) |
| ETIM                           | EC002599                                     |
| UNSPSC 24.0                    | 26121600                                     |