



Product information

Erem®

1522NB

Code No. : **T1522NB**

Cutting head for 1500 BSF - side cutter - pointed relieved head

- This is the narrowest head shape.
- The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas.

Technical Data

Cut:	Flush
Weight:	32 g / 1.12 oz.
Length of cutting edges:	9 mm / .354 Inch
Head width:	10,5 mm / .413 Inch
Head thickness:	6,5 mm / .256 Inch
Max. cutting capability	
Copper wire:	Ø 1,2 mm / .047 Inch

Erem Cutters and Tip Cutters

- Internal patented Erem Magic Spring
 - Reduce costs by long life
 - Constant spring force
 - Guarantees more than 1 million operations
- High precision screw joint
 - Smooth jaw action with no play
 - Smooth cutting operation with no jaw overlapping
- Induction-hardened cutting edges in Rockwell hardness 63 - 65 HRC for exceptionally long life

- EMOS maximum opening stop
limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles
for high comfort, better grip and added safety
- Erem cut:
Options for semi flush, full flush or super flush cuts

Weller®