



## GENERAL INFORMATION

pitch:	7,5 mm
housing height:	18,40 mm
housing depth:	20.6 mm
dimensional class:	high
wire section:	6.0 mm <sup>2</sup> / 10 AWG
clamp opening size:	3.2 × 3.9 mm
wire stripping:	max 8.5 mm
operating temperature:	-40°C ÷ +130°C

## ELECTRICAL CHARACTERISTICS

current:	41A
voltage:	750V
test voltage:	3 kVrms/60s

## MECHANICAL CHARACTERISTICS

screw:	M3
max. torque:	0.5 Nm / 4.5 in.lbs

## APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	30A factory / 30A field
wire section:	-	-	300V
torque:	-	-	20÷10AWG
FILE:	-	-	7.2Lb-in
			E178356

## MATERIALS

housing:	PA - UL 94 V0
----------	---------------

## AVAILABLE COLOURS

screw:  
clamp/spring:  
terminal:

Galvanized steel  
Nickeled copper alloy  
Tin-plated copper alloy



other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
1	MVL471-7,5-V	N/A	N/A	N/A
..	MVL47..-7,5-V	N/A	N/A	N/A