

har-modular female str. pre-ass L81,28




Image is for illustration purposes only. Please refer to product description.

Part number	C0 25 200 0000 0025
Specification	har-modular female str. pre-ass L81,28
HARTING eCatalogue	https://harting.com/C02520000000025

Identification

Category	Connectors
Series	har-modular®
Element	Female connector
Specification	Pre-assembled connector
Description of the contact	Straight

Version

Installed modules	2x 02529000003	https://harting.com/02529000003
	3x 02529031301	https://harting.com/02529031301
Length	81.18 mm	
Termination method	Reflow soldering termination (THR)	
	Wave soldering termination	
Connection type	Motherboard to daughtercard	
	Mezzanine	

Technical characteristics

Insulation resistance	$>10^{11} \Omega$
Limiting temperature	-55 ... +125 °C (during reflow soldering max. +240 °C for 15 s)
Performance level	1
	acc. to IEC 60603-2
Mating cycles	≥ 500
Isolation group	I ($600 \leq CTI$)
Hot plugging	No



Pushing Performance
Since 1945

Technical characteristics

Moisture Sensitivity Level (MSL)	1 acc. to ECA/IPC/JEDEC J-STD-020D
----------------------------------	------------------------------------

Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	Black Yellow
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained


Specifications and approvals

UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Railway classification	F1/I2 acc. to NFF 16-101/102

Commercial data

Packaging size	120
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140660380
eCl@ss	27460201 PCB connector (board connector)
UNSPSC 24.0	39121415

Mating conditions



To ensure reliable connections and prevent unnecessary damage, please refer to the application data diagrams. These recommendations are set out in IEC 60603-2.

The connectors should not be coupled and decoupled under electrical load.