


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® SVRE	29.11.2013

With incised sealing ring for adjustment to several cable diameters
Fewer sizes need to be kept in stock



Robust

Application range

Brass cable gland with hexagonal fitting and variable incised sealing ring.

Design

PG connection thread

Note

Refer to SKINDICHT® EV for additional accessories

Counter nut to be used: SKINDICHT® SM

Remark

Viton® is a registered trademark of DuPont de Nemours

Photographs are not to scale and do not represent detailed images of the respective products.



Technical Data

Caution:

The installation dimensions
can be found in appendix T21

On request:

Available with long connection thread
Available with PG 11 to 36 with VITON® incised ring

Material:

Body: nickel-plated brass
Incised seal: CR

Protection rating:

IP 54

Temperature range:

-20°C to +80°C


Product Management	Document: LAPP_PRO1081EN.pdf	1 / 3
--------------------	------------------------------	-------




SKINDICHT® SVRE

29.11.2013

Part number	Article designation / size	Incised sealing ring ØF (mm)	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)
SKINDICHT® SVRE					
52005540	SVRE 9	5/8	17 / 15	22,6	6.0
52000310	SVRE 11	7/10/12.5	20 / 18	22,6	6.0
52000320	SVRE 13,5	7/10.5/13/16	22 / 20	26,1	6.5
52000330	SVRE 16	8/10.5/13.5/16	24 / 22	27,1	6.5
52000340	SVRE 21	11/15/18/20	30 / 28	29,6	7.0
52000350	SVRE 29	19/23/27/31	40 / 37	32,6	8.0
52000360	SVRE 36	25/28/31/35	50 / 47	38,6	9.0
52005550	SVRE 42	35.5/39/42.5/46	57 / 54	43,6	10.0
52005560	SVRE 48	40.5/44/47/50.5	64 / 60	45,1	10.0

U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® SVRE	29.11.2013



Product Management	Document: LAPP_PRO1081EN.pdf	3 / 3
--------------------	------------------------------	-------