


Item no.: 745-3153
 Product description: PCB TERMINAL STRIP 2 SOLDER PINS / POLE 3 POLE PIN
 SPACING 7.5 MM / 0.295 IN without jumper slot



Produkt kann von Bild abweichen / product may differ

Packing unit 120 2*60 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	6.187 g
Color	gray
No. of connection Points	3
No. of potentials	3
pole count	3
Height	19 mm
Height	0.748 in
Width	21.5 mm
Width	0.846 in
Depth	19.4 mm
Depth	0.764 in
Pin spacing from	7.5 mm
Pin spacing from	0.295 in
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	6 kV
Current intensity EN	32 A
Pollution degree	2

Measured voltage EN	1000 V
Measured shock voltage	6 kV
Current intensity EN	32 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm²]	0.08 - 4 mm²
Wiring method	solid
Cross section [mm²]	0.08 - 4 mm²
Cross section [mm²]	0.25 - 2.5 mm²
Cross section [mm²]	0.25 - 2.5 mm²
Cross section [AWG]	28 - 12 AWG
Strip length from	8 mm
Strip length to	9 mm
Material group	I
Customs Tariff No.	85369010
Country of Origin	Schweiz
xxx-xxx/000-006	blue
xxx-xxx/000-009	light gray
xxx-xxx/000-016	green-yellow
xxx-xxx/000-017	light green



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
745-3153	CCA	NL5831	630	32	0,08-4
745-3153	cURus	E45172	300	20	28-12
745-3153	KEMA	2076500.01	630	32	0,08-4

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected