


Quectel Antenna Portfolio

Overview

November, 2020

Duty of Confidentiality

The Receiving Party shall keep confidential all documentation and information provided by Quectel, except when the specific permission has been granted by Quectel. The Receiving Party shall not access or use Quectel's documentation and information for any purpose except as expressly provided herein. Furthermore, the Receiving Party shall not disclose any of the Quectel's documentation and information to any third party without the prior written consent by Quectel. For any noncompliance to the above requirements, unauthorized use, or other illegal or malicious use of the documentation and information, Quectel will reserve the right to take legal action.




Overview



**External Rubber
Antenna**



**External GNSS
Antenna**



**Internal GNSS
Antenna**




SMD Antenna



Waterproof Antenna



Combined Antenna



**Embedded
FPC&PCB Antenna**



RF Cable


External Rubber Antenna

RF Cable

External Waterproof Antenna

Embedded Antenna

GNSS Antenna



5G/4G/3G/2G Antenna



OC: YE0001BA

Frequency (MHz)	600–6000
Peak Gain (dBi)	5.0
VSWR	≤ 3.0
Average Efficiency	600–960 MHz: 40 %; 1710–2690 MHz: 50 %; 3000–5900 MHz: 50 %
Antenna Shape	Straight or bent
Application	5G/4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	221x 26.95x13.5
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

OC: YE0007AA

Frequency (MHz)	600–5000
Peak Gain (dBi)	5.0
VSWR	≤ 3.0
Average Efficiency	600–960 MHz: 40 %; 1710–2690 MHz: 50 %; 3000–5900 MHz: 45 %
Antenna Shape	Straight or bent
Application	5G/4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	152.4x 21.79x14.49
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

5G/4G/3G/2G Antenna



OC: YE0003AA

Frequency (MHz)	699–5000
Peak Gain (dBi)	2
VSWR	≤ 5
Average Efficiency	699–960 MHz: 40 %; 1710–2690 MHz: 50 %; 3000–5000 MHz: 45 %
Antenna Shape	Straight or bent
Application	5G/4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	190 × 16Ø
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

OC: YE00025AA

Frequency (MHz)	698–960, 1710–5000MHz
Peak Gain (dBi)	2
VSWR	≤ 5.0
Average Efficiency	698–960 MHz: 38 %; 1710–2690 MHz: 45 %; 3000–5000 MHz: 35 %
Antenna Shape	Straight or bent
Application	5G/4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	199 × 22Ø
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

4G/3G/2G Antenna



OC: YE0009AA

Frequency (MHz)	824–2690
Peak Gain (dBi)	3.0
VSWR	≤ 3
Average Efficiency	824–960 MHz: 30 %; 1710–2690 MHz: 50 %
Antenna Shape	Straight or bent
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	190 × 16
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

OC: YGL001AA

Frequency (MHz)	700–960, 1710–2690
Peak Gain (dBi)	3
VSWR	≤ 5
Average Efficiency	700–960 MHz: 30 %; 1710–2690 MHz: 60 %
Antenna Shape	Straight or bent
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	196.2 × 16 × 13
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G Antenna



OC: YE0005AA

Frequency (MHz)	824–2700
Peak Gain (dBi)	3.0
VSWR	≤ 3.0
Average Efficiency	824–960 MHz: 35 %; 1710–2700 MHz: 70 %
Antenna Shape	Bent in fixed right-angle
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	115 × 8
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module



OC: YE0002AA

Frequency (MHz)	699–2700
Peak Gain (dBi)	3.0
VSWR	≤ 3
Average Efficiency	699–960 MHz: 50 %; 1710–2700MHz: 60 %
Antenna Shape	No bending
Application	4G/3G/2G
Connector	RP-SMA Male (with center receptacle)
Impedance (Ω)	50
Size (mm)	174.6 × 19.2
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G Antenna



OC:YDX001AA

Frequency (MHz)	824–2690
Peak Gain (dBi)	5
VSWR	≤ 2
Average Efficiency	824–960 MHz: 35 %; 1710–2690 MHz: 50 %
Antenna Shape	Straight or bent
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	208 × Ø 12
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G Antenna



OC: YE0012AA

Frequency (MHz)	824–960, 1710–2690
Peak Gain (dBi)	4
VSWR	≤ 2.0
Average Efficiency	824–960 MHz: 25 %; 1710–2690MHz: 50 %
Antenna Shape	Straight
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	116.5 × 21.7 × 5.6 with default cable length 250mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module



OC: YE0010AA

Frequency (MHz)	698–2700
Peak Gain (dBi)	3.0
VSWR	≤ 3.0
Average Efficiency	698–960 MHz: 25 %; 1710–2700MHz: 50 %
Antenna Shape	Straight
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	152 × 18 × 5.9 with default cable length 1000 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

NB-IoT/3G/2G Antenna



OC: YE0011AA

Frequency (MHz)	824–960, 1710–2170
Peak Gain (dBi)	3
VSWR	≤ 3.5
Average Efficiency	824–960 MHz: 20 %; 1710–2170 MHz: 40 %
Antenna Shape	bent
Application	NB-IoT/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	50 × Ø 10
Quectel Module	Module Series: LPWA/UMTS/GSM/GPRS



OC: YE0008AA

Frequency (MHz)	824–960, 1710–2170
Peak Gain (dBi)	3
VSWR	≤ 3.5
Average Efficiency	824–960 MHz: 20 %; 1710–2170 MHz: 40 %
Antenna Shape	bent
Application	NB-IoT/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	52 × Ø 10
Quectel Module	Module Series: LPWA/UMTS/GSM/GPRS


External Rubber Antenna

RF Cable

External Waterproof Antenna

Embedded Antenna

GNSS Antenna



SMA to MHF I



OC: YM0002AA

Frequency (MHz)	0–6000
Insertion Loss (dB)	≤ 2
VSWR	≤ 1.5
Connector	SMA Female (with center receptacle) to IPEX I
Cable Diameter (mm)	1.13
Application	5G/4G/3G/2G/Wi-Fi/GPS
Impedance (Ω)	50
Length (mm)	93 ±2
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module



OC: YM0003AA

Frequency (MHz)	0–6000
Insertion Loss (dB)	≤ 2
VSWR	≤ 1.5
Connector	SMA Female (with center receptacle) to IPEX I
Cable Diameter (mm)	1.13
Application	5G/4G/3G/2G/Wi-Fi/GPS
Impedance (Ω)	50
Length (mm)	100 ±2
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

SMA to MHF IV



OC: YM0004AA

Frequency (MHz)	0–6000
Insertion Loss (dB)	≤ 2
VSWR	≤ 1.5
Connector	SMA Female (with center receptacle) to IPEX IV
Cable Diameter (mm)	1.13
Application	5G/4G/3G/2G/Wi-Fi/GPS
Impedance (Ω)	50
Length (mm)	100 ±2
Quectel Module	Module Series: 5G



OC: YM0005AA

Frequency (MHz)	0–6000
Insertion Loss (dB)	≤ 2
VSWR	≤ 1.5
Connector	SMA Female (with center receptacle) to IPEX IV
Cable Diameter (mm)	1.13
Application	5G/4G/3G/2G/Wi-Fi/GPS
Impedance (Ω)	50
Length (mm)	150 ±2
Quectel Module	Module Series: 5G


External Rubber Antenna

RF Cable

External Waterproof Antenna

Embedded Antenna

GNSS Antenna



5G/4G/3G/2G Antenna



OC: YFS001

Frequency (MHz)	700–960, 1710–2700, 3300–3800, 4400–5000
Peak Gain (dBi)	3
VSWR	≤ 4.5
Average Efficiency	700–960 MHz: 40 %; 1710–2700 MHz: 50 %; 3300–3800MHz; 4400~5000 MHz: 50 %
Antenna Shape	Straight
Application	5G/4G/3G/2G
Connector	Type-N connector (male)
Impedance (Ω)	50
Size (mm)	300 × Ø 22.6
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

OC: YXH001AA

Frequency (MHz)	700–960, 1710–2690, 3300–5000
Peak Gain (dBi)	4.5
VSWR	≤ 4
Average Efficiency	700–960 MHz: 35 %; 1710–2690 MHz: 30 %; 3300–5000 MHz: 40 %
Antenna Shape	Magnetic
Application	5G/4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	285 × 45 with cable length 1000 mm
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12


5G/4G Antenna



OC: YB0007AA

Frequency (MHz)	700–960, 1710–2690, 3300–5000
Gain (dBi)	0 Min.
VSWR	≤ 4
Average Efficiency	700–960 MHz: 30 %; 1710–2690 MHz: 50 %; 3300–5000 MHz: 50 %
Antenna Shape	4 in 1 combination
Application	5G/4G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	Φ 120 × 43 with default cable length 500 mm
Quectel Module	Module Series: 5G/LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G Antenna



OC: YCN001AA

Frequency (MHz)	700–2700
Peak Gain (dBi)	2.5
VSWR	≤ 3.5
Average Efficiency	700–960 MHz: 30 %; 1710–2700 MHz: 50 %;
Antenna Shape	Straight
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	144 × Ø 13
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

OC: YE0006AA

Frequency (MHz)	700–2700
Peak Gain (dBi)	3.0
VSWR	≤ 2.0
Average Efficiency	700–960 MHz: 25 %; 1710–2690MHz: 50 %
Antenna Shape	Magnetic
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	318 × Ø 30 with cable length 1500 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G Antenna



OC: YKL001AA

Frequency (MHz)	Wi-Fi/BT: 2400–2500; 4G: 824–960, 1710–2690; GPS&BD: 1575.42 ±10, 1561 ±10
Peak Gain (dBi)	LNA: 28 ±2; 2G/3G/4G: 2.5; BT: 3
VSWR	≤ 3
Average Efficiency	824–960 MHz: 40 %; 1710–2690 MHz: 50 %; 2400~2500MHz: 40%
Antenna Shape	Combined antenna box
Application	4G/3G/2G/Wi-Fi/BT/GPS&BD
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	33 × 48 with default cable length 310 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

OC: YB0009AA

Frequency (MHz)	4G:824–960, 1710–2690; GPS&BD: 1575.42 ±10, 1561 ±10
Peak Gain (dBi)	LNA: 28 ±2; 2G/3G/4G: 2.5; BT: 3
VSWR	≤ 3
Average Efficiency	824–960 MHz: 40 %; 1710–2690 MHz: 50 %;
Antenna Shape	Combined antenna box
Application	4G/3G/2G/GPS&BD
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	33 × 48 with default cable length 310 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G Antenna



OC: YB0010AA

Frequency (MHz)	698–960, 1710–2690
Peak Gain (dBi)	3
VSWR	≤ 2.94
Average Efficiency	698–960 MHz: 40 %; 1710–2690 MHz: 50 %;
Antenna Shape	Combined antenna box
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	Φ 81.5 × 16 with default cable length 2000 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

OC: YB0008AA

Frequency (MHz)	4G Main: 698–960, 1710–2690; 4G DIV: 1710–2690; GNSS: 1575.42 ±5, 1561.098 ±5
Peak Gain (dBi)	LNA: 28 ±2; 2G/3G/4G: 2.94; 4G DIV: 3.96
VSWR	≤ 4
Average Efficiency	698–960 MHz: 30 %; 1710–2690 MHz: 50 %;
Antenna Shape	Combined antenna box
Application	4G/3G/2G/GPS&BD
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	Φ 84 × 17.5 with default cable length 300 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module


External Rubber Antenna

RF Cable


External Waterproof Antenna

Embedded Antenna

GNSS Antenna



5G/4G/3G/2G Antenna



OC: YF0002AA, YF0002BA, YF0002CA, YF0002DA

Frequency (GHz)	700-6G-1/700-6G-2 1700-6G-1/1700-6G-2	0.7-6 1.7-6
Peak Gain (dBi)	700-6G-1 700-6G-2 1700-6G-1 1700-6G-2	2.7 4.2 2.0 3.7
VSWR	700-6G-1 700-6G-2 1700-6G-1 1700-6G-2	≥ 1.4 ≥ 1.0 ≥ 1.0 ≥ 1.2
Average Efficiency	700-6G-1 700-6G-2 1700-6G-1 1700-6G-2	0.7-6 GHz: 35 % 0.7-6 GHz: 30 % 1700-6 GHz: 30 % 1700-6 GHz: 35 %
Application	4G/3G/2G, 2.4G/5.8G Wi-Fi	
Impedance (Ω)	50	
Size (mm)	700-6G-1 700-6G-2 1700-6G-1 1700-6G-2	60.10 × 12.25 50.25 × 20.10 41.25 × 10.25 37.35 × 9.75
Quectel Module	Typical Modules: RM500Q (Customized)	

4G/3G/2G Antenna



OC: YF0003AA

Frequency (MHz)	824–960; 1710–2690
Peak Gain (dBi)	5.0
VSWR	≤ 5
Average Efficiency	824–960 MHz: 25 %; 1710–2690 MHz: 60 %
Application	4G/3G/2G
Connector	IPEX I
Impedance (Ω)	50
Size (mm)	62.0 × 19.0 (customized cable length)
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module



OC: YF0004AA

Frequency (MHz)	824–960, 1710–2690
Peak Gain (dBi)	5.0
VSWR	≤ 4.5
Average Efficiency	824–960 MHz: 30 %; 1710–2690 MHz: 60 %
Application	4G/3G/2G
Connector	IPEX I
Impedance (Ω)	50
Size (mm)	87.17 × 20.0 (customized cable length)
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

5G/4G/3G/2G Antenna



OC: YF0005AA

Frequency (MHz)	700–6000
Peak Gain (dBi)	5.0
VSWR	≤ 2.5
Average Efficiency	700–960 MHz: 30 %; 1710–2690 MHz: 60 %; 3300–5900 MHz: 50 %
Application	5G/4G/3G/2G
Connector	IPEX I
Impedance (Ω)	50
Size (mm)	112.5 × 16.2 (customized cable length)
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

OC: YF0008AA

Frequency (MHz)	700–6000
Peak Gain (dBi)	5.0
VSWR	≤ 2.5
Average Efficiency	700–960 MHz: 30 %; 1710–2690 MHz: 60 %; 3300–5900 MHz: 50 %
Application	5G/4G/3G/2G
Impedance (Ω)	50
Connector	IPEX IV
Size (mm)	112.5 × 16.2 (customized cable length)
Quectel Module	Typical Modules: RG500Q/RM500Q/EM20/EP06/EG06/EG12/EG18/EM06/EM12

4G/3G/2G Antenna



OC: YF0006AA

Frequency (MHz)	690–960, 1710–2170, 2300–2690
Peak Gain (dBi)	6.0
VSWR	≤ 3.0
Average Efficiency	690–960 MHz: 25 %; 1710–2690 MHz: 50 %
Application	4G/3G/2G
Connector	U.FL I
Impedance (Ω)	50
Size (mm)	50 × 25 × 0.13 (customized cable length)
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module


5G/4G/3G/2G PCB Antenna



OC: YP0001AA

Frequency (MHz)	600–6000
Peak Gain (dBi)	2
VSWR	≤ 3.0
Average Efficiency	600–960 MHz: 30 %; 1710–2690 MHz: 50 %; 3300–6000 MHz: 50 %
Antenna Shape	PCB
Application	5G/4G/3G/2G
Connector	IPEX IV
Impedance (Ω)	50
Size (mm)	107.25 × 14.0 × 0.4 (customized cable length)
Quectel Module	Module Series: 5G/LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G PCB Antenna



OC: YF0007AA

Frequency (MHz)	600–960, 1427.9–1495.9, 1710–2170, 2300–2700
Peak Gain (dBi)	4.7
VSWR	≤ 5.0
Average Efficiency	600–960 MHz: 20 %; 1710–2690 MHz: 50 %;
Application	4G/3G/2G
Connector	U.FL I
Impedance (Ω)	50
Size (mm)	50 × 25 × 0.85 (customized cable length)
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

OC: YCW001AA

Frequency (MHz)	824–2690
Peak Gain (dBi)	2
VSWR	≤ 3.0
Average Efficiency	824–960 MHz: 25 %; 1710–2690 MHz: 50 %
Application	4G/3G/2G
Connector	SMA Male (with center pin)
Impedance (Ω)	50
Size (mm)	94.06 × 16.20 × 1.05 with default cable length 500 mm
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

4G/3G/2G SMD Antenna



OC: YC0003AA

Frequency (MHz)	698–960, 1695–2200, 2300–2700
Peak Gain (dBi)	5.5
VSWR	≤ 3.0
Average Efficiency	698~960 MHz: 30 %; 1695~2700 MHz: 50 %
Antenna Shape	SMD
Application	4G/3G/2G
Impedance (Ω)	50
Size (mm)	40 × 7 × 3
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module

OC: YC0001AA

Frequency (MHz)	698–960, 1710–2690
Peak Gain (dBi)	3.0
VSWR	≤ 4.0
Average Efficiency	698–960 MHz: 30 %; 1710–2690MHz: 50 %
Antenna Shape	SMD
Application	4G/3G/2G
Impedance (Ω)	50
Size (mm)	35 × 8.5 × 3
Quectel Module	Module Series: LTE-A/LPWA/LTE-Standard/GSM/GPRS/Wi-Fi/Smart Module


External Rubber Antenna

RF Cable

External Waterproof Antenna

Embedded Antenna

GNSS Antenna



GNSS Patch Antenna – Passive Ceramic Antenna




OC: YG0018AA

Center Frequency (MHz)	1575.42
Size (mm)	15 × 15 × 4
Peak Gain (dBic typ.)	2.5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1

OC: YG0008AA

Center Frequency (MHz)	1575.42
Size (mm)	18 × 18 × 4
Peak Gain (dBic typ.)	2.5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1

GNSS Patch Antenna – Passive Ceramic Antenna





OC: YG0010AA

Center Frequency (MHz)	1575.42
Size (mm)	25 × 25 × 4
Peak Gain (dBic typ.)	4.5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1

OC: YG0019AA

Center Frequency (MHz)	1575.42
Size (mm)	36 × 36 × 4
Peak Gain (dBic typ.)	5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1

GNSS Antenna – Passive L1&L5 Antenna



OC: YC0008AA

Center Frequency (MHz)	1575.42, 1176.45
Size (mm)	30 × 5 × 5
Peak Gain (dBic typ.)	2
Polarization	Linear
Max Zenith Axial Ratio (dB)	N/A
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1/L5

OC: YG0030AA

Center Frequency (MHz)	1575.42, 1176.45
Size (mm)	25 × 25 × 4 (lower layer); 18 × 18 × 4 (upper layer)
Peak Gain (dBic typ.)	3 @ 52 × 52 mm Patch Ground
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1/L5

GNSS Antenna – Passive L1&L5 Patch Antenna



OC: YG0033AA

Center Frequency (MHz)	1575.42, 1176.45
Size (mm)	38 × 38 × 6.16 (lower layer); 25 × 25 × 4.76 (upper layer)
Peak Gain (dBic typ.)	4.0 @ 50 × 50 mm Patch Ground
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1/L5

OC: YVO001AA

Center Frequency (MHz)	1575.42, 1176.45
Size (mm)	38 × 38 × 6.16 (lower layer); 25 × 25 × 4.76 (upper layer)
Peak Gain (dBic typ.)	4.0 @ 50 × 50 mm Patch Ground
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	L1/L5

GNSS Antenna – External Passive Antenna



OC: YYS001CA

Center Frequency (MHz)	1559–1575–1602
Size (mm)	50.9 × 38.6 × 17
Peak Gain (dBic typ.)	2
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dBi)	N/A
Max Overall Gain (dBi)	N/A
Operation Voltage (V)	N/A
Application	GPS L1/BD B1/GLONASS L1
Connector	SMA Male (with center pin), cable length 1500 mm

GNSS Patch Antenna – Active Patch Antenna




OC: YCN001BA

Center Frequency (MHz)	1575–1602
Size (mm)	15 × 15 × 6.9
Peak Gain (dBic typ.)	2.0
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	/
LNA Gain (dB)	28
Max Overall Gain (dB)	30.4
Operation Voltage (V)	3.0 ±0.6
Application	GPS L1/BD B1/GLONASS L1
Connector	IPEX I

OC: YG0021AA

Center Frequency (MHz)	1560–1605
Size (mm)	18.4 × 18.4 × 8.86
Peak Gain (dBic typ.)	2.5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	/
LNA Gain (dB)	19
Max Overall Gain (dB)	21.5
Operation Voltage (V)	3.0 ±0.1
Application	GPS L1/BD B1/GLONASS L1
Connector	IPEX I

GNSS Patch Antenna – Active Patch Antenna



OC: YG0015AA

Center Frequency (MHz)	1575–1615
Size (mm)	25 × 25 × 8.25
Peak Gain (dBic typ.)	2
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	/
LNA Gain (dB)	27
Max Overall Gain (dB)	29
Operation Voltage (V)	3.0 ±0.6
Application	GPS L1/GLONASS L1
Connector	IPEX I



OC: YG0016AA

Center Frequency (MHz)	1561, 1575, 1602, 1606
Size (mm)	36.01 × 36.01 × 10.25
Peak Gain (dBic typ.)	4.5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	/
LNA Gain (dB)	27
Max Overall Gain (dB)	31.5
Operation Voltage (V)	3.3 ±0.6
Application	GPS L1/BD B1/GLONASS L1
Connector	SMA Male (with center pin), RG174 L = 130 mm

GNSS Patch Antenna – Active L1&L5 Patch Antenna



OC: YJW001AA

Center Frequency (MHz)	1164–1189, 1559–1610
Size (mm)	50 × 50 × 21.62
Peak Gain (dBic typ.)	2.5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dB)	28
Max Overall Gain (dB)	30.5
Operation Voltage (V)	2.7–5.5
Application	GPS L1/L5 /BD B1/GLONASS L1
Connector	SMAMale (with center pin), cable length 300 mm

GNSS Antenna – Active L1&B1 Antenna




OC: YG0026AA

Center Frequency (MHz)	1561, 1575
Size (mm)	50.3 × 38.4 × 17.1
Peak Gain (dBic typ.)	5
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dB)	28
Max Overall Gain (dB)	33.5
Operation Voltage (V)	2.8–3.6
Application	GPS L1/BD B1/GLONASS L1
Connector	SMA Male (with center pin); Cable length 5030 mm

OC: YLY001CA

Center Frequency (MHz)	1568 ± 10
Size (mm)	45.5 × 38 × 13.5
Peak Gain (dBic typ.)	3
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dB)	28
Max Overall Gain (dB)	31.5
Operation Voltage (V)	2.7–5.5
Application	GPS L1/BD B1
Connector	SMA Male (with center pin); Cable length 1000 mm

GNSS Antenna – Active L1&L5 Antenna



OC: YB0017AA


Center Frequency (MHz)	GPS L1/L5, BDB1/ B2, GLONASS L1
Size (mm)	61.5 × 56.5 × 23
Peak Gain (dBic typ.)	4
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dB)	22
Max Overall Gain (dB)	26
Operation Voltage (V)	3–5
Application	GPS L1/L5 /BD B1/GLONASS L1
Connector	SMA Male (with center pin); Cable length 3000 mm

OC: YG0028AA

Center Frequency (MHz)	1561–1602, 1166–1186
Size (mm)	Φ 54 × 38
Peak Gain (dBic typ.)	2
Polarization	R.H.C.P
Max Zenith Axial Ratio (dB)	3
LNA Gain (dB)	14.5 ±5
Max Overall Gain (dB)	16.5 ±5
Operation Voltage (V)	1.7 ±3.3
Application	GPS L1/L5 /BD B1/GLONASS L1
Connector	SMA Male (with center pin); Cable length 3000 mm

Thank you!

Building 5, Shanghai Business Park Phase III (Area B), No.1016
Tianlin Road, Minhang District, Shanghai 200233, China
Tel: +86-21-5108 6236
Email: info@quectel.com
Website: www.quectel.com

 <https://www.linkedin.com/company/quectel-wireless-solutions>

 <https://www.facebook.com/quectelwireless>

 https://twitter.com/Quectel_IoT