

## Han 24HPR VarioShell-2x24HPR-Set0



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 10 40 124 1000                                                                |
| Specification      | Han 24HPR VarioShell-2x24HPR-Set0                                             |
| HARTING eCatalogue | <a href="https://harting.com/10401241000">https://harting.com/10401241000</a> |

### Identification

|                             |                                 |
|-----------------------------|---------------------------------|
| Category                    | Hoods / Housings                |
| Series of hoods/housings    | Han <sup>®</sup> HPR VarioShell |
| Type of hood/housing        | Complete set                    |
| Description of hood/housing | Angled                          |

### Version

|                      |                                                             |
|----------------------|-------------------------------------------------------------|
| Size                 | 24 HPR VS                                                   |
| VarioShell level 1   | 1x 24 B                                                     |
| VarioShell level 2   | 1x 24 B                                                     |
| Locking type         | Screw locking                                               |
| Field of application | Hoods/housings for harsh outdoor environments               |
| Details              | Please note the installation manual.                        |
| Pack contents        | Bulkhead mounted housing<br>Mounting cover<br>Fixing screws |

### Technical characteristics

|                                  |                                                              |
|----------------------------------|--------------------------------------------------------------|
| Tightening torque                | 4 Nm Mounting cover<br>12 Nm Fixing screws<br>12 Nm PE screw |
| Limiting temperature             | -40 ... +125 °C                                              |
| Note on the limiting temperature | For use as a connector according to IEC 61984.               |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                                        |      |
|----------------------------------------|------|
| Degree of protection acc. to IEC 60529 | IP66 |
|                                        | IP67 |
|                                        | IP68 |
|                                        | IP69 |

## Material properties

|                         |                                           |
|-------------------------|-------------------------------------------|
| Material (hood/housing) | Aluminium die-cast<br>Corrosion resistant |
| Surface (hood/housing)  | Powder-coated                             |
| Colour (hood/housing)   | RAL 9005 (jet black)                      |
| Material (seal)         | NBR                                       |

## Specifications and approvals

|                |                              |
|----------------|------------------------------|
| Specifications | IEC 61984                    |
|                | IEC 61373 Category 1 Class B |
| Approvals      | CE                           |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 3 g                                      |
| Country of origin              | China                                    |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140175587                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |
| ETIM                           | EC000437                                 |
| UNSPSC 24.0                    | 39121466                                 |