8-968973-1 <

AMP | AMP MCP 2.8, AMP MCP Connector System

TE Internal #: 8-968973-1 Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 15 Position, .197 in [5 mm] Centerline, Wire & Cable, Cable Mount (Free-Hanging), Hybrid

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > AMP Unsealed Connector Housing



Connector System: Wire-to-Board, Wire-to-Wire

Number of Positions: 15

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 5 mm [.197 in]

Sealable: No

All AMP Unsealed Connector Housing (176)

Features

Product Type Features

Mixed & Hybrid Connector

No

Connector Shape

Rectangular

Connector System	Wire-to-Board, Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	15
Number of Rows	3
Electrical Characteristics	
Operating Voltage	28 VDC
Nominal Voltage Architecture	12 V, 24 V
Body Features	
Cable Exit Angle	180°
Connector & Keying Code	A

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 15 Position, .197 in [5 mm] Centerline, Wire & Cable, Cable Mount (Free-Hanging), Hybrid



Contact Features

Contact Size	2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF
Centerline (Pitch)	5 mm[.197 in]
Dimensions	
Connector Height	24 mm[.945 in]
Product Width	31 mm[1.22 in]
Product Length	31 mm[1.22 in]
Row-to-Row Spacing	5.5 mm[.217 in]
Usage Conditions	
Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 – 120 °C[-40 – 248 °F]
Packaging Features	
Packaging Quantity	1200
Packaging Method	Carton
Other	
Serviceable	No
Connector Position Assurance Capable	No
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant

C For support call+1 800 522 6752

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 15 Position, .197 in [5 mm] Centerline, Wire & Cable, Cable Mount (Free-Hanging), Hybrid





China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts








Also in the Series AMP MCP 2.8

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 15 Position, .197 in [5 mm] Centerline, Wire & Cable, Cable Mount (Free-Hanging), Hybrid








PCB Headers & Receptacles(1)

Also in the Series AMP MCP Connector System



Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 15 Position, .197 in [5 mm] Centerline, Wire & Cable, Cable Mount (Free-Hanging), Hybrid



Customers Also Bought



TE Part #1-967628-1 AMP Unsealed Connector Housing

TE Part #3-1813099-2 2.5mm SOCKET HSG ASSEMBLY (GREEN 3POS)



TE Part #936184-1 BULB CONN 2P PLUG ASSY IVORY TE Part #6-1355512-7 47 WAY ABS CONNECTOR

Documents

Product Drawings

MCP2.8 GEH 15P

English

MCP2.8 GEH 15P

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_8-968973-1_F.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_8-968973-1_F.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_8-968973-1_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English