

Technical drawing of a reel-to-reel tape, showing two views: a top view (reel) and a side view (tape).

**Top View (Reel):**

- Overall diameter: REEL DIA. REF.
- Feed direction: FEED DIRECTION (indicated by an arrow pointing right).
- Central hole: .500 [12.7] DIA. HOLE THRU
- Three large, irregularly shaped holes are distributed around the central hole.

**Side View (Tape):**

- Width: WIDTH
- Feed direction: FEED DIRECTION (indicated by an arrow pointing right).
- Pitch:  $\pm .005$  [ $\pm 0.15$ ]
- Top edge thickness:  $\pm .005$  [ $\pm 0.15$ ]
- Top edge hole diameter: .059 [1.5] DIA. HOLE (TYP.)
- Top edge hole spacing: .157 [4.0]
- Top edge hole diameter:  $\pm .005$  [ $\pm 0.15$ ]
- Top edge hole spacing: .079 [2.0]
- Top edge hole diameter: .787 [20.0]
- Top edge hole spacing: .413 [10.5] REF.
- Bottom edge thickness: .016 [0.4] REF.

TAPE AND REEL SPECIFICATIONS:

MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER  
ANSI/EIA-481 STANDARD  
1.732 [44.0] WIDE; 1.260 [32.0] PITCH

13.0 [330.2] DIA. 200 PIECES OF  
PART NO. 1082 PER REEL.

<b>KEYSTONE ELECTRONICS CORP.</b> www.keyelco.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME 20mm SM COIN CELL HOLDER ON TAPE			
MATERIAL AS NOTED			
FINISH AS NOTED		DRN BY NT	DATE 3.19.09
		APP'D LN	SCALE X
TOLERANCES INCH [MM] DECIMAL ±.015 [± 0.38] ANGULAR ± 1° UNLESS OTHERWISE SPECIFIED		CODE C/M	DWG NO. 1082TR