



Pushing Performance
Since 1945

M12 A-cod 5-pol st/st m/f PUR 4.0m Can



Image is for illustration purposes only. Please refer to product description.

Part number	21 34 787 5572 040
Specification	M12 A-cod 5-pol st/st m/f PUR 4.0m Can
HARTING eCatalogue	https://harting.com/21347875572040

Identification

Category	System cabling
Series	Circular connectors M12
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	M12 A-coding Male Straight
Connector 2	M12 A-coding Female Straight
Type of cable	Copper cable (round)

Version

Cable length	4 m
Number of cores	4
Core structure	2x AWG 22 2x AWG 24
Coding	A-coding

Technical characteristics

Limiting temperature	-25 ... +80 °C
----------------------	----------------

Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Black
RoHS	compliant with exemption



Pushing Performance
Since 1945

Material properties

RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead

Commercial data

Packaging size	1
Net weight	0.25 g
Country of origin	Germany
European customs tariff number	85444290
GTIN	5713140264540
eCl@ss	27060311 Assembled sensor actuator-line
ETIM	EC002599
UNSPSC 24.0	26121604