

Reducing bridge - RB PTPOWER 35-ST(2,5/4) - 3030900

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Reducing bridge, for bridging of PTPOWER 35 to ST or PT ..N terminal blocks with nominal cross section of 2.5 mm² and 4 mm², pitch: 10.8 mm, length: 4.8 mm, width: 17.8 mm, number of positions: 2, color: red

The figure shows a similar product



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 055626 012360
GTIN	4055626012360
Weight per Piece (excluding packing)	0.008 kg
Custom tariff number	85389099
Country of origin	Poland

Technical data

Technical data

Color	red
Material	PA 6.6
Number of positions	2
Pitch	10.8 mm
Length	4.8 mm
Height	56 mm
Width	17.8 mm
Flammability rating according to UL 94	V0
Maximum load current	45 A

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

Reducing bridge - RB PTPOWER 35-ST(2,5/4) - 3030900

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141140
eCl@ss 5.1	27141140
eCl@ss 6.0	27141140
eCl@ss 7.0	27141140
eCl@ss 8.0	27141140
eCl@ss 9.0	27141140

ETIM

ETIM 2.0	EC000489
ETIM 3.0	EC000489
ETIM 4.0	EC000489
ETIM 5.0	EC000489
ETIM 6.0	EC000489

UNSPSC

UNSPSC 6.01	30211829
UNSPSC 7.0901	39121426
UNSPSC 11	39121426
UNSPSC 12.01	39121426
UNSPSC 13.2	39121426