

Data sheet

264-220

**4-CONDUCTOR EEX E II MINIATURE THROUGH TERMINAL BLOCK CENTRE
MARKING
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**



Technical data

Package size 100 pieces.

| | |
|---------------------------------------|---------------------|
| Cross section from [mm ²] | 0.5 mm ² |
| Cross section to [mm ²] | 2.5 mm ² |
| Cross section from [AWG] | 20 AWG |
| Cross section to [AWG] | 12 AWG |
| Number of strands | 2 |
| Voltage UL | 600 V |
| Voltage CSA | 600 V |
| Current UL | 20 A |
| Current CSA | 20 A |
| Measured voltage EN | 750 V |
| Current intensity EN | 23 A |
| Weight | 6.08 g |
| Color | light grey |
| Wiring type | Front-entry |
| No. of connection Points | 4 |
| No. of potentials | 2 |
| Height | 24.5 mm |
| Height | 0.96 in |
| Width | 10 mm |
| Width | 0.394 in |
| Depth | 32 mm |
| Depth | 1.26 in |
| Strip length from | 8 mm |

Data sheet

264-220

**4-CONDUCTOR EEX E II MINIATURE THROUGH TERMINAL BLOCK CENTRE
MARKING
FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

| | |
|-----------------|---------|
| Strip length to | 9 mm |
| Strip length | 0.33 in |

Data sheet

264-220

4-CONDUCTOR EEX E II MINIATURE THROUGH TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

| Approval | Voltage | Current | Approval number | Notes |
|--------------|---------|---------|------------------|-------|
| BKI | 250 | 23 | 94B1-034U | |
| BKI-Ex | 750 | 23 | BKI-Ex-99.C.216U | |
| BV | | | 07436/C0 | |
| CSA | 600 | 20 | 18677-23 | |
| cURus-EX | 600 | 20 | E185892 | |
| DEMKO | | 24 | 120040/120039/04 | |
| FTZU | | | 08Q041/Ex91.0159 | |
| GOSENERGO-Ex | 750 | 23 | 99.041 | |
| KEMA | 750 | | 94.7117.01 | |
| KOPALNIA-EX | 750 | 23 | KDBNr00.E.235U | |
| KR | 800 | 24 | HMB05880-EL002 | |
| NEMKO | 750 | | L94015 | |
| PTB | 750 | 23 | IECExPTB04.0003U | |
| PTB | 750 | 23 | PTB98Atex3129U | |
| SEMKO | | | 9404012 | |
| SEV-EX | 275 | 23 | 97,550142,1 | |
| UL | 600 | 20 | E45172 | |
| VDE | 660 | | 3945ÜG,BL.2 | |

Data sheet

264-220

4-CONDUCTOR EEX E II MINIATURE THROUGH TERMINAL BLOCK CENTRE MARKING FRONT-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

Accessories

Item number

| | |
|--|-------------------------------|
| ALTERNATE COMB TYPE JUMPER BAR INSULATED | 280-492 |
| ALUMINIUM CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK | 210-296 |
| COMB TYPE JUMPER BAR INSULATED | 264-402 |
| COVER CARRIER TYPE 1 | 709-167 |
| COVER TYPE 1 | 709-153 |
| END AND INTERMEDIATE PLATE 4 MM / 0.157 IN THICK | 264-370 |
| Individual wire jumpers | individual jumper |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-002 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-005 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-006 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-007 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-012 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-017 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-023 |
| MINIATURE WSB QUICK MARKING SYSTEM PLAIN | 248-501/000-024 |
| Open individual wire jumpers ends | individual jumper open end |
| OPERATING STICKER FOR FRONT-ENTRY MINIATURE RAIL-MOUNTED TERMINAL BLOCKS | 210-291 |
| OPERATING TOOL FITTED FOR SERIES 264, 280, 281 | 209-130 |
| OPERATING TOOL INSULATED | 280-432 |
| OPERATING TOOL INSULATED | 280-433 |
| SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN | 210-257 |
| SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN | 210-258 |
| SCREWDRIVER Type 2, bar (3,5 x 0,5) mm | 210-120 |
| SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm | 210-620 |
| SCREWLESS END STOP FOR WSB QUICK MARKERS | 249-101 |
| SEPARATOR FOR EEX E / EEX I APPLICATIONS 4 MM / 0.157 IN THICK | 264-367 |
| SPARE FIXING / RETAINING SCREWS | 209-196 |
| SPARE KNURLED NUT | 210-549 |
| STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK | 210-111 |
| STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK | 210-295 |
| STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK | 210-541 |
| STEEL CARRIER RAIL 15 X 5.5 MM, 1 MM / 0.039 IN THICK | 210-542 |
| SYRINGE CONTENT: 20 ml ALU-PLUS CONTACT PASTE | 249-130 |