

1. Product Overview

USR-G800V2 support wired WAN port, LAN port, WLAN network, and 4G network interface, support serial port to network data transmission function.

2. Product Features

- Support 4 wired LAN ports and 1 wired WAN port
- Support 1 WLAN
- Support Mini-PCIE interface of 4G communication module
- Support LED status monitoring (display power supply, Work, WAN, LAN, WIFI, 4G network mode and signal strength status)
- Supports transparent data transfer from RS232 to the network
- Support SSH, Telnet, Web multi-platform management configuration
- Support one-click restore factory settings
- Wired network ports all support 10/100Mbps
- Support for multiple VPN Client (the PPTP, L2TP/GRE/OPENVPN/SSTP), and support the VPN encryption.
- Support APN automatic network checking, 2/3/4g standard switching, SIM information display, support APN dedicated network card
- Support wired wireless multi-network simultaneous online, multi-network intelligent switching backup function
- Support mandatory portal (WIFIDOG), this feature needs to be customized according to customer requirements
- Support dynamic domain name (DDNS), static routing, PPPOE, DHCP, static IP function.
- Support firewall, NAT, DMZ host, access control black and white list, IP speed limit, MAC speed limit
- Support QOS, traffic service, can limit speed according to the interface
- NTP support, built-in RTC
- Support external hardware watchdog design to ensure system stability

3. Product Specifications


Operation band				
Network type		-E	-AU	-A
4G	FDD-LTE	1/3/5/7/8/20	1/2/3/4/5/6/7/8/28	1/3
	TDD-LTE	38/39/40/41	40	38/39/40/41
3G	WCDMA/HSPA/UMTS	1/8	1/2/5/8	1/8
2G	GPRS/GSM/EDGE	3/8	2/3/5/8	3/8

Item	Info	
Product	USR-G800V2	
Ethernet	WAN	WAN*1
	LAN	LAN*4
	Rate	10/100Mbps, Auto MDI/MDIX
WIFI	Wifi	Support 802.11b/g/n

	Antenna	Wifi antenna
	Distance	150m (open field)
SIM card	SIM/USIM card	3V/1.8V SIM card
Antenna	antenna	Full frequency chuck antenna
Button	Reload	Recovery to factory setting
Status light	Status light	Power, WIFI, signal strength, WAN, LAN
Serial port	RS232	*1
	Function	Transparent transmission
Temperature	Work temperature	-20° C~+70° C
	Storage temperature	-40° C~+125° C
Humidity	Work humidity	5%~95%
	Storage humidity	1%~95%
Power	Power	DC 9~36V
	Current	Under DC12V power supply, average 170mA, maximum 289mA

4. Product Dimensions

Unit: mm



5. Contact Us

Company: Jinan USR IOT Technology Limited

Address: Floor 11, Building 1, No. 1166 Xinluo Street, Gaoxin District, Jinan, Shandong, 250101, China

Web: www.usriot.com

Support: h.usriot.com

Email: sales@usr.cn

Tel: 86-531-88826739/86-531-55507297

6. Disclaimer

This document provide the information of USR-G800V2 products, it hasn't been granted any intellectual property license by forbidding speak or other ways either explicitly or implicitly. Except the duty declared in sales terms and conditions, we don't take any other responsibilities. We don't warrant the products sales and use explicitly or implicitly, including particular purpose merchantability and marketability, the tort liability of any other patent right, copyright, intellectual property right. We may modify specification and description at any time without prior notice.

7. Update History

2019-01-28 V1.0.1 established