



Barrier terminal block - Closed - Modular version - Pitch 10mm - 2÷3 poles

GENERAL INFORMATION

pitch:	10 mm
housing height:	13,50 mm
housing depth:	16 mm
dimensional class:	medium
wire section:	2x2.5 mm ² / 2x14 AWG
clamp opening size:	
wire stripping:	max 11 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	25A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M3.5
max. torque:	0.8 Nm / 7.2 in.lbs

APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	25A factory / 20A field
wire section:	-	-	300V
torque:	-	-	12÷26AWG
FILE:	-	-	7.2Lb-in
			E178356

MATERIALS

housing:	PA - UL 94 V0
----------	---------------

AVAILABLE COLOURS

screw:
clamp/spring:
terminal:

Galvanized steel
Galvanized iron
Tin-plated copper alloy

GN^(STD) **GY** **BK** **BL** **RD** **YL** **OG**

other colours:

upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MTS212-10-C	N/A	N/A	N/A
3	MTS213-10-C	N/A	N/A	N/A
..	MTS21..-10-C	N/A	N/A	N/A