

Data sheet Product LA HB 6 300 48



Cooling aggregates>Cooling aggregates with axial fan


190 x 66 mm, with axial fan,
high performance cooling aggregate

- compact construction by means of connected extruded profiles
- excellent efficiency by means of flow-optimised hollow fin structure
- powerful axial fans
- double-sided precise milled semiconductor mounting surfaces
- different width dimensions, customised machinings, surfaces, fan types and fan voltages upon request

Features

width:	190 mm
height:	66 mm
length:	300 mm
thermal resistance:	0.06 - 0.027 K/W
surface:	• aluminium natural/degreased/cutting edges not deburred (by the metre not degreased/cutting edges not deburred) • mounting area(s) milled flat

Technical Drawing



Fan

type: ADDA AS06024

dimensions:	60x60x38 mm
tension:	24 V DC
power inout:	36 W
max. air volume:	145 m³/h
temperature range:	-10°C... +70°C
noise level:	69.5 dB(A)
speed:	16.000 min⁻¹
weight:	125 g
failure rate (L ₁₀):	70.000 h (40°C)
type:	ADDA AS06048
dimensions:	60x60x38 mm
tension:	48 V DC
power inout:	36 W
max. air volume:	145 m³/h
temperature range:	-10°C... +70°C
noise level:	69.5 dB(A)
speed:	16.000 min⁻¹
weight:	125 g
failure rate (L ₁₀):	70.000 h (40°C)
type:	ADDA AS06012
dimensions:	60x60x38 mm
tension:	12 V DC
power inout:	36 W
max. air volume:	145 m³/h
temperature range:	-10°C... +70°C
noise level:	69.5 dB(A)
speed:	16.000 min⁻¹

weight:

125 g

failure rate (L₁₀):

70.000 h (40°C)

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de