


Material and Finish:

1. Insulator Material: L.C.P.+30% Glass Filled
UL94V-0, Color: Black
2. Contact Material: Brass(C2680-EH), t=0.2mm
3. Shell Material: Brass(C2680 1/2H), t=0.5mm
4. Contact Area Plated: 15u" Gold For One Side
Plated Over 50u" Nickel
5. Solder Area Plated: 100u" Tin Plated For Double Sides
Over 50u" Nickel
6. Shell Plated: 100u" Nickel Plated
7. Current Rating: 0.5 Amp Min.
8. Insulation Resistance: Unmated: 100 Mohms Min.
Mated: 10 Mohms Min.
9. Contact Resistance: 10 mohms Max.
10. Dielectric Withstanding Voltage: 300V AC
11. Operation Temperature: -55°C to +85°C
12. Control Dimensions Indicated From ©

PRODUCT NUMBER:

206B-S A B N
1 2 3 4

1. Solder Tail Type
S: SMT Type
2. Contact Plating
A: 15u" Gold Plating
3. Metal Shell Type
B: SMT Metal shell
4. Shell Plating
N: Nickel plated



UNLESS OTHERWISE SPECIFIED TOLERANCE				DRAWN NAME:			
ANGLES	ANG.	±5°			www.attend.com.tw		
LINEAR	0.	±0.3					
	0.0	±0.25					
	0.00	±0.20	DRAWN NAME:		HDMI Connector With Flange		
SCALE	AS SHOWN	UNIT: mm	CHECKED		Solder Tail: SMD Type, Shell: SMD Type		
DRAWN	Willis	2012/10/25	APPROVED		Ken		
REV.	DESCRIPTION	DATE	REV.	DESCRIPTION	DATE	PRODUCT NO.	206B-SABN
1			1			FILE NAME	206B-SABN_B_1