


Item no.: 721-605/018-042  
 Product description: MALE CONNECTOR WITH SNAP-IN MOUNTING FOOT 5  
 POLE PIN SPACING 5 MM / 0.197 IN 100% PROTECTED  
 AGAINST MISMATING WITH PRECEDING GROUND  
 CONTACT WITH MOUNTING FEET 209-137 ON TS 35  
 SHEET THICKNESS 0.6x1.2 MM 3.5 MMØ



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	3 (Multi Conn. System)
Weight	7.861 g
Color	light gray
No. of connection Points	5
No. of potentials	5
pole count	5
Height	14.3 mm
Height	0.563 in
Width	28.2 mm
Width	1.11 in
Depth	27.5 mm
Depth	1.083 in
Pin spacing from	5 mm
Pin spacing from	0.197 in
Pollution degree	2
Measured voltage EN	320 V

Measured shock voltage	4 kV
Current intensity EN	12 A
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	12 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Wiring method	solid
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Cross section [mm <sup>2</sup> ]	0.25 - 1.5 mm <sup>2</sup>
Cross section [mm <sup>2</sup> ]	0.25 - 2.5 mm <sup>2</sup>
Cross section [AWG]	28 - 12 AWG
Strip length from	8 mm
Strip length to	9 mm
Material group	I
xxx-xxx/033-000	Strain relief plate 20 mm



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
721-605/018-042	ABS	04-HG469925/1-PDA	250	12	0,08-2,5
721-605/018-042	CCA	5764	250	12	0,08-2,5
721-605/018-042	CSA	154112-1466354	300	15	28-12
721-605/018-042	KEMA	2083746.02	250	12	0,08-2,5
721-605/018-042	KR	HMB05880-EL003	250/400	12/16	2,5
721-605/018-042	LR	96/20035	250	12	0,08-2,5
721-605/018-042	UR	E45171	600	20	12
721-605/018-042	UR	E45172	300	15	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected