



Pushing Performance
Since 1945

Keystone Patch panel, loaded



Image is for illustration purposes only. Please refer to product description.

Part number	20 82 405 0001
Specification	Keystone Patch panel, loaded
HARTING eCatalogue	https://harting.com/20824050001

Identification

Category	Connectors
Series	preLink®
Element	Patch panel

Version

Size	Keystone version
Fixing	In 19" racks acc. to IEC/DIN EN 60 297-3-100 (DIN 41 494-1)
Details	This item requires additional a termination block. Please select these under "Matching Products".
Pack contents	24 preLink® RJ45 keystone jack 24 terminal modules for AWG 22 / 23 24 cable ties

Technical characteristics

Conductor cross-section	0.22 ... 0.32 mm²
Conductor cross-section [AWG]	AWG 24 ... AWG 22
Transmission characteristics	Cat. 6 Class E _A up to 500 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s 5 Gbit/s 10 Gbit/s
Limiting temperature	-40 ... +85 °C
Degree of protection acc. to IEC 60529	IP20
Vibration resistance	5.72 m/s² acc. to IEC 61373 Category 1 Class B



Pushing Performance
Since 1945

Technical characteristics

Shock resistance 5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B

Material properties

Material (insert)	Steel sheet
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained

Specifications and approvals

Specifications	EN 45545-2
Approvals	DNV GL
PROFINET	Yes

Commercial data

Packaging size	1
Net weight	1,607.2 g
Country of origin	Czechia
European customs tariff number	85389099
GTIN	5713140135727
eCl@ss	27440292 Connector component (accessories)
ETIM	EC002943
UNSPSC 24.0	39121400