


Item no.: 734-304/019-000
 Product description: MALE CONNECTOR WITH FIXING FLANGE 4 POLE PIN SPACING 3.5 MM / 0.138 IN 100% PROTECTED AGAINST MISMATING FOR SCREW OR SIMILAR MOUNTING TYPES FOR PARALLEL OR PERPENDICULAR MOUNTING



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

| | |
|--------------------------|------------------------|
| Product group | 3 (Multi Conn. System) |
| Weight | 4.384 g |
| Color | light gray |
| No. of connection Points | 4 |
| No. of potentials | 4 |
| pole count | 4 |
| Height | 13.4 mm |
| Height | 0.528 in |
| Width | 28.8 mm |
| Width | 1.134 in |
| Depth | 22.3 mm |
| Depth | 0.878 in |
| Pin spacing from | 3.5 mm |
| Pin spacing from | 0.138 in |
| Pollution degree | 2 |
| Measured voltage EN | 160 V |
| Measured shock voltage | 2.5 kV |

| | |
|------------------------|--------|
| Current intensity EN | 10 A |
| Pollution degree | 2 |
| Measured voltage EN | 320 V |
| Measured shock voltage | 2.5 kV |
| Current intensity EN | 10 A |



| | |
|----------------------------------|----------------------------|
| Connection method | CAGE CLAMP® CONNECTION |
| Cross section [mm ²] | 0.08 - 1.5 mm ² |
| Wiring method | solid |
| Cross section [mm ²] | 0.08 - 1.5 mm ² |
| Cross section [mm ²] | 0.25 - 1.5 mm ² |
| Cross section [mm ²] | 0.25 - 1.5 mm ² |
| Cross section [AWG] | 28 - 14 AWG |
| Strip length from | 6 mm |
| Strip length to | 7 mm |
| Material group | I |
| xxx-xxx/032-000 | Strain relief plate 6 mm |



| Item no. | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|-----------------|------------------|-------------------|-------------|-------------|-----------------------------------|
| 734-304/019-000 | ABS | 04-HG469925/1-PDA | 250 | 10 | 0,5-1,5 |
| 734-304/019-000 | CCA | NL5641 | 250 | 10 | 0,5-1,5 |
| 734-304/019-000 | CSA | 154112-1465035 | 300 | 10 | 28-14 |
| 734-304/019-000 | KEMA | 2077592.02 | 250 | 10 | 0,5-1,5 |
| 734-304/019-000 | UR | E45171 | 250 | 10 | 28-14 |
| 734-304/019-000 | UR | E45172 | 300 | 10 | 28-14 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected