



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
 Contact Factory (modshop@hammondmfg.com) for quotes
 Solid models of this enclosure available in STEP or IGES.
 (Part number and text placement/orientation on our products are subject to change,
 we do not recommend using them as a locating reference for modification purposes)

| NOTE | |
|---|--|
| Purchased assembly includes box, lid and 8 cover screws. | |
| Box and lid are made from Diecast Aluminum Alloy. | |
| Silicone Gasket supplied with liquid resistant enclosure. | |
| Recommended Torque: 50-55 cN.m [71-78 ozf.in] | |
| Recommended Torque with Gasket : 25-30 cN.m [36-43 ozf.in] | |

| PART NUMBERS | |
|---|--------------|
| 1590FFL Enclosure | |
| Natural Finish Enclosure | 1590FFL |
| Black Textured Enclosure | 1590FFLBK |
| 1590FFL Liquid Resistant Enclosure (Silicone Gasket) | |
| Natural Finish Enclosure | 1590WFFL |
| Black Textured Enclosure | 1590WFFLBK |
| ACCESSORIES | |
| Liquid Resistant Cover Screws | |
| Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring] | 1590WMS100 |
| Black Stainless Steel Cover Screws (Pkg 100) [6-32 x 1/2" With O-Ring] | 1590WMS100BK |
| Standard Cover Screws | |
| Plated Cover Screws (Pkg 100) [6-32 x 1/2"] | 1590MS100 |
| Black Cover Screws (Pkg 100) [6-32 x 1/2"] | 1590MS100BK |

HAMMOND MANUFACTURING®
1590FFL
 www.hammondmfg.com

Dimensions:
 mm
 [inches]