

Printview: Female connector; with ejectors; 5x2-pole; pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; 2 rows; with coding fingers to be cut off - Item No.: 713-1105/037-000

**WAGO**® online catalog / eShop

**Female connector; with ejectors; 5x2-pole; pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; 2 rows; with coding fingers to be cut off**

Item No.: 713-1105/037-000



Female connector; with ejectors; 5x2-pole; pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; 2 rows; with coding fingers to be cut off

## Marking

RoHS ✓  
Compliant

## Business data

Supplier	WAGO
Item no.	713-1105/037-000
GTIN / EAN	4045454806170
Content	1
Order amount	50
Customer item number	

## Notes

*Item description: Universal connection for all conductor types Unique, compact, double-row connector system for conductor cross sections up to 1.5mm<sup>2</sup> High-density, "wire-to-board" connectors for use in very confined spaces Centered strain relief plate anchors conductors, while acting as convenient connection and disconnection handle. It also provides easy access to operating slots – even when wired. With coding fingers and 100% protected against mismatching*

## Technical data

### Miscellaneous


No. of poles	10
Pin spacing	3.5 mm (0.138 in %)
Total number of connection points	10
Total number of potentials	10

<b>Technical data</b>	
<i>Color</i>	<i>black</i>
<i>Ratings according to 1</i>	<i>IEC/EN 60664-1</i>
<i>Rated voltage (III / 3) [V]</i>	<i>80 [V]</i>
<i>Rated surge voltage (III / 3) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated voltage (III / 2) [V]</i>	<i>160 [V]</i>
<i>Rated surge voltage (III / 2) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated voltage (II / 2) [V]</i>	<i>250 [V]</i>
<i>Rated surge voltage (II / 2) [kV]</i>	<i>2.5 [kV]</i>
<i>Nominal current [A]</i>	<i>10 [A]</i>
<i>Number of individual connection objects at the product</i>	<i>1</i>
<i>Number of levels</i>	<i>2</i>
<i>Connection technology</i>	<i>CAGE CLAMP®</i>
<i>Number of connection points</i>	<i>1</i>
<i>Actuation type</i>	<i>Betätigungswerkzeug</i>
<i>Solid sizes</i>	<i>0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG</i>
<i>Fine-stranded wires</i>	<i>0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG</i>
<i>Fine-stranded wires with insulated ferrule</i>	<i>0.25 ... 1 mm<sup>2</sup> / ...</i>
<i>Fine-stranded wires with uninsulated ferrule</i>	<i>0.25 ... 1 mm<sup>2</sup> / ...</i>
<i>Strip length</i>	<i>6 ... 7 mm / 0.24 ... 0.28 in</i>
<i>Strip length (1) [in]</i>	<i>0.26 [in]</i>
<i>Material group</i>	<i>II</i>
<i>Insulating material</i>	<i>Glass-fiber-reinforced polyamide (PA66 GF)</i>
<i>Flammability rating per UL 94</i>	<i>V0</i>
<i>Limit temperature range</i>	<i>-60 ... 100 C</i>
<i>Clamping spring material</i>	<i>Chrome-nickel spring steel (CrNi)</i>
<i>Contact material</i>	<i>Copper alloy</i>
<i>Contact plating</i>	<i>tin-plated</i>
<i>Fire load [MJ]</i>	<i>0.111 [MJ]</i>
<i>Weight [g]</i>	<i>6.27 [g]</i>
<i>Width</i>	<i>26 mm / 1.024 in</i>
<i>Height</i>	<i>18.8 mm / 0.74 in</i>
<i>Length</i>	<i>16 mm / 0.63 in</i>


Printview: Female connector; with ejectors; 5x2-pole; pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; 2 rows; with coding fingers to be cut off - Item No.: 713-1105/037-000

---

## Images & drawings



Printview: Female connector; with ejectors; 5x2-pole; pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; 2 rows; with coding fingers to be cut off - Item No.: 713-1105/037-000



#### Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.