



UT39 SERIES General Digital Multimeters

UT39C ■ UT39E



EN:61010-1

EN:61326-1



■ UT39C



■ UT39E

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT39C	UT39E
Model			
DC Voltage (V)	200mV/2V/20V/200V/1000V	±(0.5%+1)	±(0.05%+3)
AC Voltage (V)	2V/20V/200V/750V	±(0.8%+3)	±(0.5%+10)
DC Current (A)	2mA/200mA/20A	±(0.8%+1)	±(0.5%+5)
AC Current (A)	2mA/200mA/20A	±(1%+3)	±(0.8%+10)
Resistance (Ω)	200Ω/2KΩ/20KΩ/2MΩ/20MΩ	±(0.8%+1)	±(0.3%+1)
Capacitance (F)	2nF/200nF/20μF	±(4%+3)	
	2nF/20nF/200nF/20μF		±(0.4%+10)
Frequency (Hz)	2KHz/20KHz	±(1.5%+5)	±(1.5%+5)
Temperature (°C)	-40 °C ~ 1000°C	±(2%+8)	
Features			
Display Count		1999	19999
Manual Range		✓	✓
Diode		✓	✓
Transistor		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	61mm × 32mm
Product Color	Red and Grey
Product Net Weight	310g (Including Holster)
Product Size	172mm × 83mm × 38mm
Standard Accessories	UT39C-Battery, Test Lead, Point Contact Temperature Probe, Holster UT39E-Battery, Test Lead, Holster
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	40 PCs
Standard Carton Measurement	598mm × 418mm × 340mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	2.2Kg