
Item no.:	264-344
Product description:	4-CONDUCTOR TERMINAL BLOCK WITH SNAP-IN MOUNTING FOOT FOR SHEET THICKNESS 0.6-1.2 MM 3.5 MMØ FOR ALUMINUM RAIL 210-154 OR WITH MOUNTING ADAPTER 209-120 FOR TS 35 SUITABLE FOR EX I APPLICATIONS



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	9 (Std Chassis Mt Blocks)
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP® CONNECTION
Number of strands	2
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	6.234 g
Color	blue
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	1
Height	22 mm
Height	0.867 in

Width	10 mm
Width	0.394 in
Depth	32 mm
Depth	1.26 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
264-344	ABS	04-HG476174/1-PDA	800	24	2,5
264-344	BV	07436/C0			0,08-2,5
264-344	CCA	NL6511	800	24	2,5
264-344	CSA	18677-23	600	20	26-12
264-344	DNV	E-9215	800	24	2,5
264-344	GL	17295-00HH	800	24	2,5
264-344	KEMA	2110272.04	800	24	2,5
264-344	KR	HMB05880-EL002	800	24	
264-344	LR	92/20242(E5)	800	24	2,5
264-344	RMR	11130002	800	24	2,5
264-344	UR	E45172	300	20	28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected