

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>EPIC® H-A 10 TG</b>	<b>13.01.2016</b>

These connectors are attractive because of their compact housing.  
Small and space-saving for narrow available space



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof



#### Info

Non-slip ridges for comfortable disconnecting

#### Application range

Machine and equipment manufacturing  
Control engineering  
Electronic laboratory

#### Product features

Hood, low version  
Bolts for single lever  
Straight cable entry  
Versions with / without neck

#### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

#### Technical Data

Material:

Housing: aluminium alloy, grey  
Lever: zinc-plated steel  
Sealing: NBR


Protection rating:

IP 65 (latched)

Temperature range:

-40°C to +100°C, short-term up to +125°C



Product Management	Document: LAPP_PRO341EN.pdf	1 / 3
--------------------	-----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	 <b>LAPP GROUP</b>
	EPIC® H-A 10 TG	13.01.2016

Part number	Article description	M	PG	Neck
H-A housing: hood (straight cable entry, bolts for single lever)				
10446000	H-A 10 TG 13,5		13.5	yes
10446100	H-A 10 TG 16		16	yes
19446000	H-A 10 TG M20	20		
19446100	H-A 10 TG M25	25		

Product Management	Document: LAPP_PRO341EN.pdf	2 / 3
--------------------	-----------------------------	-------

U.I. Lapp GmbH	PRODUCT INFORMATION	 <b>LAPP GROUP</b>
	EPIC® H-A 10 TG	13.01.2016



Product Management	Document: LAPP_PRO341EN.pdf	3 / 3
--------------------	-----------------------------	-------