



■ SPECIFICATIONS

	Range	UT681L	UT681C	UT681HDMI	Description
Test function	To test for: RJ45/RJ11	√			
	To test for: RJ45/RJ11/BNC		√		Need to use RJ45 to BNC adaptor
	To test for: HDMI/MINI-HDMI			√	
	Fast test mode	√	√		LED1~LED8, LED_G
	Slow test mode	√	√		LED1~LED8, LED_G
	Scan test mode			√	LED1~LED19, LED_S
	Full display test mode			√	LED1~LED19, LED_S
	To test for the case of short circuit, crossover, open circuit, etc.	√	√	√	
	Ethernet cable: shielded/ unshielded test	√	√	√	
	Manual shutdown function	√	√	√	
	Auto shutdown function	√	√	√	No operation within 10 minutes, the device will shut down automatically
	Single key operation	√	√	√	
	Power supply: 9V battery	√	√	√	
Low battery detection	√	√	√	Less than 7.2V	
Application environment	Working temperature: 0~40°C	√	√	√	
	Storage temperature: -10~50°C	√	√	√	
	Working humidity: 20~80%RH	√	√	√	
	Storage humidity: 10~90%RH	√	√	√	
	Altitude: ≤2000 meters	√	√	√	
Safety standard	CE EN61326-1: 2013; EN61326-2-2: 2013	√	√	√	

■ GENERAL CHARACTERISTICS

Product color	Red and grey
Product net weight	Transmitter: 87g; receiver: 51g
Product size	Transmitter: 102mm x 62mm x 28mm; receiver: 102mm x 37mm x 28mm
Standard accessories	9V battery, BNC to RJ45 adaptor (UT681C)
Standard individual packing	Gift box, English manual
Standard quantity per carton	40pcs
Standard carton measurement	455mm x 410mm x 225mm
Standard carton gross weight	UT681L : 6.4kg; UT681C : 8.7kg; UT681HDMI : 9.5kg