



Recommended P.C.B Layout

MATERIAL

Insulator : NYLON 66 UL94V-0

Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 1000MΩMin.

Contact Resistance : 20mΩMax.

Withstanding Voltage : 800V AC/minute

Operation Temperature : -25°C to + 85°C

725-7 1- xx T W 06
1 2 3 4 5 6

1. 7: Green Product
2. 1: Straight type
2: Right angle type
3. No. of contacts
4. G: Gold flash
T: Tin plated
5. B: Black Insulator
W: Nature Insulator
6. Pinrex internal code.



Poles	DIM A	DIM B
6	4.00	7.90
8	6.00	9.90
10	8.00	11.90
12	10.00	13.90
14	12.00	15.90
16	14.00	17.90
18	16.00	19.90
20	18.00	21.90
22	20.00	23.90
24	22.00	25.90
26	24.00	27.90
28	26.00	29.90
30	28.00	31.90
32	30.00	33.90



E	顏色修正	2021/03/09	TOLERANCE UNITS : mm	OLD PART NO.		TITLE 2.0mm CRIMP STYPE CONNECTORS WAFER	 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.		
D	增加工作溫度	2016/04/29		DRAWER	CHECK				
C	REVISE DESCRIPTION	2012/08/06		姜文慧	李劍				
B	REVISE SIZE	2012/02/28							
A	RELEASE	2007/03/21							
REV.	DESCRIPTION	DATE	SCALE NONE	SIZE A4	SHEET 1 OF 1	REV. E	APP'D 李劍	NEW PART NO. 725-71-xxTW06	DRAW NO. 725-71-xxTW06(E版)