

Item no.: 285-150
Product description: 2-conductor through terminal block



Produkt kann von Bild abweichen / product may differ

Packing unit 5 pieces

RoHS compliant

| | |
|----------------------------------|-------------------------|
| Cross section [mm ²] | 10 - 50 mm ² |
| Cross section [AWG] | 8 - 1 AWG |
| Connection method | POWER CAGE CLAMP |
| Cross section [mm ²] | 10 - 70 mm ² |
| Cross section [AWG] | 8 - 2/0 AWG |
| Wiring method | f |
| Connection method | POWER CAGE CLAMP |
| Measured voltage EN | 1000 V |
| Measured shock voltage | 8 kV |
| Pollution degree | 3 |
| Current intensity EN | 150 A |
| Weight | 157.24 g |
| Color | grey |
| Wiring type | Side-entry |
| No. of connection Points | 2 |
| No. of potentials | 1 |
| Height | 87 mm |
| Height | 3.425 in |
| Width | 20 mm |

| | |
|-------|----------|
| Width | 0.787 in |
| Depth | 94 mm |
| Depth | 3.701 in |



| | |
|--------------------|----------|
| Strip length from | 30 mm |
| Strip length to | 30 mm |
| Strip length | 1.18 in |
| Customs Tariff No. | 85369010 |
| Country of Origin | Polen |



| Item number | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|-------------|------------------|----------------|-------------|-------------|-----------------------------------|
| 285-150 | CCA | NL6390 | 1000 | 150 | 50 |
| 285-150 | CSA | 114112-1327714 | 600 | 150 | 8-1/0 |
| 285-150 | KEMA | 2116735.01 | 1000 | 150 | 50 |
| 285-150 | UR | E45172 | 600 | 150 | 8-2/0 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected