

## InduCom 25p special for cable K screw



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 61 03 001 0217                                                                |
| Specification      | InduCom 25p special for cable K screw                                         |
| HARTING eCatalogue | <a href="https://harting.com/61030010217">https://harting.com/61030010217</a> |

### Identification

|                             |                        |
|-----------------------------|------------------------|
| Category                    | Hoods / Housings       |
| Series                      | D-Sub                  |
| Identification              | InduCom                |
| Type of hood/housing        | Shell housing          |
| Description of hood/housing | Without internal earth |

### Version

|                         |                                                                                                                                                                                                                                    |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                    | D-Sub 3                                                                                                                                                                                                                            |
| Version                 | Top entry                                                                                                                                                                                                                          |
| Number of cable entries | 1                                                                                                                                                                                                                                  |
| Cable entry             | 1x                                                                                                                                                                                                                                 |
| Strain relief           | In case of strain relief for one cable, DIN 41612 insert or cable clamps must be used.<br>In case of strain relief for one or two cables, D-Sub insert and cable clamp or crimp flange and crimp ferrule combination must be used. |
| Locking type            | Knurled screw Thread 4-40 UNC                                                                                                                                                                                                      |
| ground connection       | Without internal grounding block                                                                                                                                                                                                   |
| 2 parts                 | Yes                                                                                                                                                                                                                                |
| Separable               | Yes                                                                                                                                                                                                                                |
| Pack contents           | Fixing screws                                                                                                                                                                                                                      |

### Technical characteristics

|                      |                                            |
|----------------------|--------------------------------------------|
| Tightening torque    | 0.4 Nm cover screw<br>0.4 Nm Locking screw |
| Limiting temperature | -55 ... +125 °C                            |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                                        |      |
|----------------------------------------|------|
| Degree of protection acc. to IEC 60529 | IP30 |
|----------------------------------------|------|

## Material properties

|                                      |                      |
|--------------------------------------|----------------------|
| Material (hood/housing)              | Zinc die-cast        |
| Material (screw)                     | Steel, nickel plated |
| Length                               | 60.7 mm              |
| Width                                | 51.7 mm              |
| Height                               | 25 mm                |
| RoHS                                 | compliant            |
| ELV status                           | compliant            |
| China RoHS                           | e                    |
| REACH Annex XVII substances          | Not contained        |
| REACH ANNEX XIV substances           | Not contained        |
| REACH SVHC substances                | Not contained        |
| California Proposition 65 substances | Not contained        |

## Commercial data

|                                |                     |
|--------------------------------|---------------------|
| Packaging size                 | 10                  |
| Net weight                     | 93.38 g             |
| Country of origin              | China               |
| European customs tariff number | 85389099            |
| GTIN                           | 5713140222601       |
| eCl@ss                         | 27440213 D-Sub hood |
| ETIM                           | EC001133            |
| UNSPSC 24.0                    | 39121416            |