


Preliminary Datasheet


Dimensions mm

tolerances acc. to DIN ISO 2768-m
Toleranzen gem. DIN ISO 2768-m




angular variation of the pins up to 7,5° possible
Winkelabweichung der Anschlußpins bis zu 7,5° möglich

Schematic



Isometric

Scale 2:1
Maßstab 2:1



Marking

according to EN60062/factory code
gem. EN60062/Fertigungsstätte

MEDER BV411 YM

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull-In	at 20°C	7		10,7	VDC
Test equipment		PK 055			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		A - NO			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
Switching voltage	DC or Peak AC			180	V
Carry current	DC or Peak AC			1	A
Switching current	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive			150	mOhm
Housing material		PBT glass fibre reinforced			
Case color		blue			
Sealing compound		Epoxy resin			

Environmental data	Conditions	Min	Typ	Max	Unit
Shock	1/2 sine, duration 11ms, in 3 axis			30	g
Vibration	from 10 - 2000 Hz			20	g
Ambient temperature		-20		85	°C
Storage temperature		-35		85	°C
Cleaning		fully sealed			