

TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: PBT
FLAMMABILITY RATING: UL94-V0
COLOR: WHITE
CONTACT MATERIAL: COPPER ALLOY
CONTACT TYPE: STAMPED
CONTACT PLATING: SELECTIVE GOLD
SHIELDING: BRASS Ni PLATED
QUALITY CLASS: 1500 MATING CYCLES



ENVIRONMENTAL
OPERATING TEMPERATURE: -40°C UP TO +105°C
COMPLIANCE: LEAD FREE AND ROHS

ELECTRICAL
CURRENT RATING: 1.5 A
WORKING VOLTAGE: 30 V
INSULATOR RESISTANCE: >1000 MΩ
DIELECTRIC WITHSTANDING VOLTAGE: 750 VAC/MIN
CONTACT RESISTANCE: 20 mΩ MAX

STANDARD
CERTIFIED: E323964

SOLDERING
JEDEC LEAD FREE WAVE SOLDERING

PACKAGING
TRAY

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15	 WÜRTH ELEKTRONIK	DESCRIPTION: DUAL USB 2.0 TYPE A HORIZONTAL	SIZE A4
M	09-AVR-15	PCB THICKNESS	QP					
L	27-OCT-14	REVIEW	QL					
K	23-MAY-13	CURRENT RATING	QL					
J	15-FEV-13	DESIGNATION	AR	APPROVAL: NPr	UNIT: MM	WERI PART NO: 614 008 260 21		
I	25-SEP-12	DESCRIPTION	GG		SCALE:			
H	09-JAN-12	NEW DRAWING	GG		SHEET: 1/1			
REV	DATE	FILE	BY		DRAW: NPr			

