

# 9047.0102

## Product number

Actuation type	direkt
Weight	6.100 g
Switching function	Umschalter (SPDT)
Material fixed contact	Ag
Number of poles	1 - pole
Connections	Lötanschluss, abgedichtet
Mechanical life endurance	5E4
Contact system	5E4
Rating IEC	4 A 30 V DC 5 A 48 V AC

<b>Contact resistance (new condition)</b>	< 20 mOhm	
<b>Insulation resistance (new condition)</b>	> 1000 MOhm	
<b>Voltage strength at 250 V</b>	Function insulation / Basic insulation Reinforced insulation Small contact distance	null V null V > 1000 V
<b>Actuators</b>	Schraubhülse, silbermetallic, CuZn verchromt Hebel, CuZn verchromt	
<b>Housing description</b>	Sockel: olivgrün, DAP Bügelplatte: Stahl rostfrei Zahnscheibe: Duroplast (Sockel) / Stahl verzinkt chromatiert (Bügelplatte) Sicherungsring: Duroplast (Sockel) / Stahl verzinkt chromatiert (Bügelplatte) Gewindebuchse: CuZn vernickelt, 6-Kantmuttern aus CuZn vernickelt	
<b>Connection surface</b>	Bearing connection External connection	versilbert versilbert
<b>Contact material</b>	Ag	
<b>Contact type</b>	Abhebekontakt	
<b>Miscellaneous</b>	NKK-Nr.: M-2012 LLW 01 weitere Schraubhülsen 9090.02.. in anderen Farben siehe Zusatzteile	

**Type of fastening**

Zentralbefestigung M6 x 0.75

All information subject to possible technical changes