



UHF C1 Gen2 Tag

UHF On metal tag

U-1195



- * On metal UHF tag
- * on Aluminum foil and Aluminum material and on any metal
- * High performance reading range. OVER 3M (Base on ALN-9900)
- * Available in high-yield volume with stable process.

Protocol & Memory

Protocol	EPC global C1G2/ISO 180000-6C
Mode of operation	Passive
Memory	32 bit kill passwords 32 bit access passwords Typical 96 bits EPC Number23

Structure

Frequency range	Global (860-960MHZ)
U-1195 Dimensions	: 135x22x14mm
Readin range	: over 3m (on metal testing)
Operating temperature	: -20°c to +85c
Storage temperature	: 25°c at 40%RH

**Address: Unit B1, 3/F., Mai Shun Industrial Building,
18-24 Kwai Cheong Road, Kwai Chung ,
New Territories, Hong Kong.**
Phone: 0852- 27702330 Fax: 0852- 23886226



SUNBEST TECHNOLOGY CO.,LTD

ROHS

IP67

Application :Inventory management

*Government official document management

* Theftproof product management

- Instrument management
- Property management



**Address: Unit B1, 3/F., Mai Shun Industrial Building,
18-24 Kwai Cheong Road, Kwai Chung ,
New Territories, Hong Kong.
Phone: 0852- 27702330 Fax: 0852- 23886226**