


Model:	LP551230	Overcharge Detection Voltage(V)	4.28±0.05
Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	130	Overdischarge Detection Voltage(V) 过放电保护电压(V)	3.0±0.1
Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	140	Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 0.3 (A)	constant (A) 持续 0.1 (A)
Nominal Voltage 标称电压 (V)	3.7	Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A)	constant (A) 持续 (A)
Internal impedance 内阻 (≅) (mΩ, AC 1KHz)	450	Battery protection Related Value: (相关的电池保护值) If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
Charge Temp. 充电温度 (°C)	0~45		
Discharge Temp. 放电温度 (°C)	-20~60		
Humidity (湿度)	65±20%		

Remark (备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).
 2. Rols compliant (严格按照ROHS要求生产).

		Drawn:	zhuhaoran	Revise No.:	E4-2009
		Checked 1:	Shannon	Projection:	
EEMB BATTERY		Checked 2:		Page:	1/1
		Approved:		Scale:	1.5 : 1
Title	LP551230-PCM-LD/	Draw Date:	2014/02/06	Unit:	mm



1 2 3 4 5 6