

CONFIDENTIAL

VERTRAULICH

Alle Rechte bei Marquardt, auch fuer den Fall von Schutzrechtsanmeldungen. Jede Veruegungsbefugnis, wie Kopier- und Weitergaberecht, bei uns.

©

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF MARQUARDT. WITHOUT THEIR CONSENT IT MAY NOT BE REPRODUCED OR GIVEN TO THIRD PARTIES.

	1	2	3	4	
A	recommended cut-out for snap-in fixing (edge opposite to snap-in direction)		wall thickness	length of cut-out	width of cut-out
			0.75 to 1.25	19.2-0.1	12.9+0.1
			1.25 to 2	19.4-0.1	12.9+0.1
			2 to 3	19.8-0.1	12.9+0.1
B					
C					
D	<p>Marking</p> <p>Ⓜ</p> <p>1803.</p> <p>6(4)/250~5E4</p> <p>10(4)250~ T100/55</p>		<p>Single pole changeover Suitable for appliances of class II</p>		
E	<p>10A 125-250V AC</p> <p>1/3HP 125V AC</p> <p>1/2HP 250V AC</p> <p>R50 Ⓜ</p> <p>Code of manufacture: place/year/week</p>				

-	-	-	1803.6222-XX
Figure	Type	Customer Part No.	Art.No.-PI
Shape and location	Angle ± 2 °	Sheet 01	
	Edge tolerance	Ident. K	Document number 18036222
Ⓜ	0-6	± 0.2	Index b
	>6-15	± 0.4	Appliance Switch
>15-30	± 0.4	All dimensions are in millimetres	
±	±		Format DIN A4
±	±	Projection	
±	±	Scale 1:1	
±	±	System NX V1872	
±	±	Replacement of	
±	±	Zg.gl.Nr.v.04.08.2005	
b	137892	MARQUARDT	
a	64510	2021/Nov/25	
Index	MEC-No.	Date (YYYY-MM-DD)	Edited by