

Data sheet Product LA V 32 300 24





Cooling aggregates>Cooling aggregates with axial fan
164,6 x 85 mm, with axial fan and air-flow chamber

Features

width:	164.6 mm
height:	85 mm
length:	300 mm
thermal resistance:	0.037 - 0.089 K/W
surface:	aluminium natural/degreased/cutting edges not deburred (by the metre not degreased/cutting edges not deburred)
operating voltage of the fan motor:	• 12 V DC • 24 V DC • 48 V DC

Technical Drawing



Fan

type:	ebmpapst 8212 JH4
dimensions:	80x80x38 mm
tension:	12 V DC
power inout:	39 W
max. air volume:	222 m³/h
temperature range:	-20°C... +70°C
noise level:	71 dB(A)
speed:	14,000 min⁻¹
weight:	200 g
failure rate (L ₁₀):	L₁₀ > 50,000 h (40°C)

type:	ebmpapst 8214 JH4
dimensions:	80x80x38 mm
tension:	24 V DC
power inout:	38 W
max. air volume:	222 m³/h
temperature range:	-20°C... +70°C
noise level:	71 dB(A)
speed:	14,000 min⁻¹
weight:	200 g
failure rate (L ₁₀):	L₁₀ > 50,000 h (40°C)

type:	ebmpapst 8218 JH4
dimensions:	80x80x38 mm
tension:	48 V DC
power inout:	36 W
max. air volume:	222 m³/h
temperature range:	-20°C... +70°C
noise level:	71 dB(A)

speed:	14,000 min⁻¹
weight:	200 g
failure rate (L ₁₀):	L₁₀ > 50,000 h (40°C)

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de