


## Dimensions



## Model number

### V3-WM-E2-10M-PUR

Cable socket, M8, LED, 3-pin, PUR cable

## Features

- Built-in LED, as operating and function indicator
- Knurled nut suitable for tool assembly
- Immunity to vibration, with mechanical latching
- Gold plated contacts
- Halogen-free
- Suitable for 2- and 3-wire technology

## Technical data

### General specifications

Number of poles	3
Connection 1	Connector, female
Construction type 1	angled
Threading 1	M8
Connection 2	free cable end

### Indicators/operating means

LED green	Operating display
LED yellow	Functional display NO

### Electrical specifications

Operating voltage	max. 24 V DC $\pm$ 15%
Operating current	max. 4 A
Volume resistance	< 5 m $\Omega$

### Ambient conditions

Ambient temperature	-25 ... 100 °C (248 ... 373 K) for temperatures over 80 °C (353 K) reduced elongation at tear
Degree of soiling	3

### Mechanical specifications

Contact elements	spring-loaded contact socket
pin diameter	1 mm
Protection degree	IP67
Material	
Contacts	CuSn / Au
Contact surface	Au
Handle	TPU, transparent
Cable	PUR
Slotted nut	CuSn / Ni
Core isolation	PP
Cable	fine-strand, flexible
Sheath diameter	Ø4.8 mm
Bend radius	> 10 x conductor diameter, appropriate for conveyor chains
Colour	grey
Cores	3 x 0.34 mm <sup>2</sup>
Conductor construction	19 x 0.15 mm Ø
Length	L 10 m
Flammability	
Contact material	94V-2
Housing	94V-2

## Electrical connection 1

