

Han TPL 800 Y-distributor shielded



Image is for illustration purposes only. Please refer to product description.

Part number	09 40 033 0902
Specification	Han TPL 800 Y-distributor shielded
HARTING eCatalogue	https://harting.com/09400330902

Identification

Category	Connector sets
Series of hoods/housings	Han® HPR TrainPowerLine
Element	Y-distributor

Version

Number of contacts	3
Field of application	Hoods/housings for harsh outdoor environments
Details	Suitable for shield currents up to max. 150 A (depending on the cable and cable gland used). EMC tested according to EN 60512-23-3.

Technical characteristics

Conductor cross-section	95 ... 185 mm ²
Rated current	800 A
Rated voltage	5,100 V DC 3,000 V AC

Material properties

Material (hood/housing)	Aluminium die-cast Corrosion resistant
-------------------------	---



Pushing Performance
Since 1945

Specifications and approvals

Specifications	EN 50124-1
	EN 50467
	IEC 61373 Category 1 Class B
	UIC 550
	UIC 552

Commercial data

Packaging size	1
Net weight	6,340 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140571501
eCl@ss	27440114 Rectangular connector (for field assembly)
ETIM	EC002636
UNSPSC 24.0	39121408