

Item no.: 770-733/007-000
 Product description: PLUG SNAP IN TYPE 3 POLE 100% PROTECTED AGAINST MISMATING WITH DIRECT CONTACT OF THE GROUND CONDUCTOR



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	20 (WINSTA)
pole count	3
Cross section [mm ²]	0.5 - 4 mm ²
Cross section [AWG]	20 - 12 AWG
Connection method	CAGE CLAMP®S Connection
Number of strands	2
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	25 A
Weight	13.053 g
Color	white
No. of connection Points	6
No. of potentials	3
Height	17.5 mm
Height	0.689 in
Width	35.5 mm
Width	1.398 in

Depth	36 mm
Depth	1.417 in
Strip length from	9 mm
Strip length to	9 mm
Strip length	0.35 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
770-733/007-000	ABS	06-HG154986/11-PDA	250	25	0,5-4,0
770-733/007-000	CCA		250	25	0,5-4,0
770-733/007-000	cURus	E45171	600	20	12
770-733/007-000	DNV	E-9217	250	25	4
770-733/007-000	GL	42875-02HH	250	25	4
770-733/007-000	KEMA		250	25	0,5-4,0
770-733/007-000	LR	02/20050(E3)	250	20	2,5
770-733/007-000	PRS	TE/1719/880590/08	250	25	0,5-4,0
770-733/007-000	PSE	Jet 0695-43009-1002	600	20	12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected