

Item no.: 280-502/281-586
Product description: TERMINAL BLOCK WITH VARISTOR AND ENDPLATE WITH DIRECT CONNECTION TO CARRIER RAIL



Produkt kann von Bild abweichen / product may differ

Packing unit 25 pieces

RoHS compliant

Product group	1 (Rail Mounted Terminal Blocks)
Nominal voltage UBN	24 V
Max. operating voltage VB max. (AC)	30 V
MAX. SURGE CURRENT IS MAX. (kA)	1 kA
Capacity	$\leq 3,5 \text{ pF}$
Protection level (AC)	93 V
Cross section [mm ²]	0.08 - 2.5 mm ²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Current intensity EN	20 A
Nominal voltage	24 V
Weight	13.1 g
Color	gray
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	1
Height	39.5 mm
Height	1.55 in
Width	10 mm

Width	0.394 in
Depth	64 mm
Depth	2.52 in



Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Customs Tariff No.	85369010
Country of Origin	Deutschland
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
280-502/281-586	BV	07436/C0			0,08-2,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected