

# BC95&BC95-G

# Difference Introduction

**NB-IoT Module Series**

Rev. BC95&BC95-G\_Difference\_Introduction\_V1.0

Date: 2018-08-28

Status: Released



**Our aim is to provide customers with timely and comprehensive service. For any assistance, please contact our company headquarters:**

**Quectel Wireless Solutions Co., Ltd.**

7<sup>th</sup> Floor, Hongye Building, No.1801 Hongmei Road, Xuhui District, Shanghai 200233, China

Tel: +86 21 5108 6236

Email: [info@quectel.com](mailto:info@quectel.com)

**Or our local office. For more information, please visit:**

<http://www.quectel.com/support/sales.htm>

**For technical support, or to report documentation errors, please visit:**

<http://www.quectel.com/support/technical.htm>

Or email to: [support@quectel.com](mailto:support@quectel.com)

**GENERAL NOTES**

QUECTEL OFFERS THE INFORMATION AS A SERVICE TO ITS CUSTOMERS. THE INFORMATION PROVIDED IS BASED UPON CUSTOMERS' REQUIREMENTS. QUECTEL MAKES EVERY EFFORT TO ENSURE THE QUALITY OF THE INFORMATION IT MAKES AVAILABLE. QUECTEL DOES NOT MAKE ANY WARRANTY AS TO THE INFORMATION CONTAINED HEREIN, AND DOES NOT ACCEPT ANY LIABILITY FOR ANY INJURY, LOSS OR DAMAGE OF ANY KIND INCURRED BY USE OF OR RELIANCE UPON THE INFORMATION. ALL INFORMATION SUPPLIED HEREIN IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.

**COPYRIGHT**

THE INFORMATION CONTAINED HERE IS PROPRIETARY TECHNICAL INFORMATION OF QUECTEL WIRELESS SOLUTIONS CO., LTD. TRANSMITTING, REPRODUCTION, DISSEMINATION AND EDITING OF THIS DOCUMENT AS WELL AS UTILIZATION OF THE CONTENT ARE FORBIDDEN WITHOUT PERMISSION. OFFENDERS WILL BE HELD LIABLE FOR PAYMENT OF DAMAGES. ALL RIGHTS ARE RESERVED IN THE EVENT OF A PATENT GRANT OR REGISTRATION OF A UTILITY MODEL OR DESIGN.

***Copyright © Quectel Wireless Solutions Co., Ltd. 2018. All rights reserved.***

# About the Document

## History

Revision	Date	Author	Description
1.0	2018-08-28	Evan WU/ Hayden WANG/ Ewent LU	Initial

---

## Contents

About the Document.....	2
Contents .....	3
Table Index.....	4
<b>1 Introduction .....</b>	<b>5</b>
<b>2 Hardware Comparison.....</b>	<b>6</b>
2.1. Pin Assignment .....	6
2.2. Pin Description and Differences .....	7
<b>3 Software Comparison.....</b>	<b>10</b>
3.1. Software Function Differences.....	10
3.2. Output/Indication Information Differences .....	11
3.3. AT Command Differences.....	12
3.3.1. Network Related Command.....	12
3.3.1.1. AT+COPS PLMN Selection.....	12
3.3.2. UDP Related Commands.....	13
3.3.2.1. AT+NSOCR Create a Socket.....	13
3.3.2.2. AT+NSOST SendTo Command (UDP Only) .....	13
3.3.2.3. AT+NSOSTF SendTo Command with Flags (UDP Only).....	14
3.3.3. UART Baud Rate Configuration Related Command .....	14
3.3.3.1. AT+NATSPEED Configure UART Port Baud Rate.....	14
3.3.4. Huawei IoT Platform Related Commands .....	15
3.3.4.1. AT+NMGS Send a Message .....	15
3.3.4.2. AT+NNMI New Message Indications .....	16
3.3.4.3. AT+QLWULDATAEX Send CON/NON Message .....	16
3.3.4.4. AT+QLWULDATASTATUS Query CON Messages Sent Status.....	17
3.3.4.5. AT+NMSTATUS Message Registration Status.....	17
3.3.4.6. AT+QSECSWT Set Data Encryption Mode .....	18
3.3.5. Other Commands.....	19
3.3.5.1. AT+NPING Test IP Network Connectivity to a Remote Host .....	19
3.3.5.2. AT+CGDCONT Define a PDP Context .....	19
3.3.5.3. AT+NCONFIG Configure UE Behaviors .....	20
3.3.5.4. AT+NUESTATS Query UE Statistics .....	21
3.3.5.5. AT+NUESTATS=RADIO Query UE Statistics .....	22
3.3.5.6. AT+NPOWERCLASS Set the Mapping for Band and Power Class.....	23
3.4. Additional AT Commands of BC95-G .....	23
<b>4 Appendix A References.....</b>	<b>25</b>

## Table Index

TABLE 1: PIN DESCRIPTION AND DIFFERENCES .....	7
TABLE 2: FIRMWARE VERSIONS .....	10
TABLE 3: SOFTWARE FUNCTION DIFFERENCES.....	10
TABLE 4: BOOT OUTPUT INFORMATION DIFFERENCES .....	11
TABLE 5: HUAWEI IOT PLATFORM FUNCTION AND INDICATION INFORMATION COMPARISON.....	11
TABLE 6: DFOTA UPGRADE INDICATION INFORMATION COMPARISON .....	11
TABLE 7: RELATED DOCUMENTS .....	25
TABLE 8: TERMS AND ABBREVIATIONS.....	25

# 1 Introduction

This document describes main differences between BC95 and BC95-G in terms of hardware and software designs, including pin assignment, software functions, AT commands comparison, etc.

## 2 Hardware Comparison

### 2.1. Pin Assignment

BC95-G is completely pin-to-pin compatible with BC95, and the pin assignment is illustrated below.




Figure 1: Pin Assignment

## 2.2. Pin Description and Differences

**Table 1: Pin Description and Differences**

Pin No.	BC95	BC95-G	Pin Description	Differences
	Pin Name	Pin Name		
1	RESERVED	RESERVED	Reserved	/
2	GND	GND	Ground	/
3	RESERVED	RESERVED	Reserved	/
4	RESERVED	RESERVED		/
5	RESERVED	RESERVED		/
6	RESERVED	RESERVED		/
7	RESERVED	RESERVED		/
8	RESERVED	RESERVED		/
9	RESERVED	RESERVED		/
10	RESERVED	RESERVED		/
11	RESERVED	RESERVED		/
12	RESERVED	RESERVED		/
13	RESERVED	RESERVED		/
14	RESERVED	RESERVED		/
15	RESET	RESET	Reset the module	/
16	RESERVED	RESERVED	Reserved	/
17	RESERVED	RESERVED		/
18	NETLIGHT	NETLIGHT	Network status indication	/
19	DBG_RXD	DBG_RXD	Receive data	/
20	DBG_TXD	DBG_TXD	Transmit data	/



21	ADC	ADC	General purpose analog to digital converter interface	/
22	RESERVED	RESERVED	Reserved	/
23	RESERVED	RESERVED		/
24	RESERVED	RESERVED		/
25	RESERVED	RESERVED		/
26	VDD_EXT <sup>1)</sup>	VDD_EXT <sup>1)</sup>	Supply 3.0V voltage for external circuit	<b>BC95:</b> I <sub>Omax</sub> =20mA (Any mode) <b>BC95-G:</b> I <sub>Omax</sub> =1mA (In PSM) I <sub>Omax</sub> =20mA (Other modes)
27	RESERVED	RESERVED	Reserved	/
28	RESERVED	RESERVED		/
29	RXD	RXD	Receive data	/
30	TXD	TXD	Transmit data	/
31	RESERVED	RESERVED	Reserved	/
32	RESERVED	RESERVED		/
33	RESERVED	RESERVED		/
34	RI	RI	Ring indicator	/
35	RESERVED	RESERVED	Reserved	/
36	RESERVED	RESERVED		/
37	RESERVED	RESERVED		/
38	USIM_VDD <sup>2)</sup>	USIM_VDD <sup>2)</sup>	Power supply for USIM card	<b>BC95:</b> 3.0V USIM card <b>BC95-G:</b> 1.8V USIM card Or 3.0V USIM card
39	USIM_RST	USIM_RST	USIM card reset	/
40	USIM_DATA	USIM_DATA	USIM card data	/

41	USIM_CLK	USIM_CLK	USIM card clock	/
42	USIM_GND	USIM_GND	USIM card ground	/
43	GND	GND	Ground	/
44	RESERVED	RESERVED	Reserved	/
45	VBAT	VBAT	Main power supply	/
46	VBAT	VBAT	of the module: VBAT=3.1V~4.2V	/
47	GND	GND	Ground	/
48	GND	GND		/
49	RESERVED	RESERVED	Reserved	/
50	RESERVED	RESERVED		/
51	GND	GND	Ground	/
52	GND	GND		/
53	RF_ANT	RF_ANT	RF antenna pad	/
54	GND	GND	Ground	/
55~58, 67~70, 75~80, 84~91	RESERVED	RESERVED	Reserved	/
59~66, 71~74, 81~83, 92~94	GND	GND	Ground	/

#### NOTES

- <sup>1)</sup> BC95 and BC95-G are different in the output current capacity of VDD\_EXT:
  - **BC95**: the maximum output current capacity of VDD\_EXT is 20mA in any operation mode.
  - **BC95-G**: the maximum output current capacity of VDD\_EXT is 1mA in PSM and 20mA in other operation modes.
- <sup>2)</sup> BC95 and BC95-G are different in the USIM card supported by USIM\_VDD:
  - **BC95**: supports 3.0V USIM card.
  - **BC95-G**: supports 1.8V and 3.0V USIM card.

# 3 Software Comparison

The software comparison between BC95 and BC95-G is based on firmware versions as listed below.

**Table 2: Firmware Versions**

	BC95	BC95-G
Firmware Version	V100R100C10B657SP5	V150R100C20B300SP2

## 3.1. Software Function Differences

**Table 3: Software Function Differences**

Function	BC95	BC95-G
Multi-Tone	Not Supported	Supported
ECID	Not Supported	Supported (For Testing Only)
OTDOA	Not Supported	Supported (For Testing Only)
IPv6	Not Supported	Supported
TCP	Not Supported	Supported
LwM2M	Not Supported	Supported
MQTT	Not Supported	Supported

## 3.2. Output/Indication Information Differences

Table 4: Boot Output Information Differences

Boot Output Information	BC95	BC95-G
Power on Boot	REBOOT_CAUSE_UNKNOWN	REBOOT_CAUSE_SECURITY_PMU_POWER_ON_RESET
Hardware Reset	REBOOT_CAUSE_SECURITY_RESET_UNKNOWN	REBOOT_CAUSE_SECURITY_RESET_PIN

Table 5: Huawei IoT Platform Function and Indication Information Comparison

Huawei IoT Platform	BC95	BC95-G
Platform Function	When the Huawei IoT platform is not used, the platform registration function needs not to be disabled.	When the Huawei IoT platform is not used, the platform registration function needs to be disabled through <b>AT+QREGSWT=2</b> .
Indication Information	No URC Indication	<b>+QLWEVTIND:0</b> <b>+QLWEVTIND:3</b>

Table 6: DFOTA Upgrade Indication Information Comparison

DFOTA Upgrade	BC95	BC95-G
DFOTA Upgrade Indication Information	FIRMWARE DOWNLOADING FIRMWARE DOWNLOADED FIRMWARE UPDATING REBOOT_CAUSE_SECURITY_RESET_UNKNOWN FIRMWARE UPDATING FIRMWARE UPDATE SUCCESS FIRMWARE UPDATE OVER	<b>+QLWEVTIND:5</b> FIRMWARE DOWNLOADING FIRMWARE DOWNLOADED FIRMWARE UPDATING REBOOT_CAUSE_SECURITY_FOTA_UPGRADE FIRMWARE UPDATE SUCCESS FIRMWARE UPDATE OVER

### 3.3. AT Command Differences

The following illustrates the differences of the AT commands supported by both BC95 and BC95-G.

#### 3.3.1. Network Related Command

##### 3.3.1.1. AT+COPS PLMN Selection

BC95	BC95-G
Test Command <b>AT+COPS=?</b>	Test Command <b>AT+COPS=?</b>
Response <b>+COPS:(2,,"46000"),,(0-2),(2)</b>	Response <b>+COPS: (2,,"46011"),(3,,"46000"),(3,,"46001"),,(0-2),(2)</b>
OK	OK

**Differences Description:** Return values of **AT+COPS=?** are different.

- **BC95**
  - 1) PLMN setting can be queried in any state of RRC, but the return value is the information that has been configured in the USIM card.
  - 2) Other AT commands can be executed before the response of **AT+COPS=?** command is returned. The maximum response time of this command is 300ms.
- **BC95-G**
  - 1) PLMN setting can only be queried when RRC is not connected, and the return value is the operator's PLMN value existing in the current network.
  - 2) Other AT commands cannot be executed before the response of **AT+COPS=?** command is returned, otherwise, an error will be reported. The maximum response time of this command is 630s.

### 3.3.2. UDP Related Commands

#### 3.3.2.1. AT+NSOCR Create a Socket

BC95	BC95-G
Write Command <b>AT+NSOCR=&lt;type&gt;,&lt;protocol&gt;,&lt;listen port&gt;[,&lt;receive control&gt;]</b>	Write Command <b>AT+NSOCR=&lt;type&gt;,&lt;protocol&gt;,&lt;listenport&gt;[,&lt;receive control&gt;[,&lt;af_type&gt;[,&lt;ip address&gt;]]]</b>
Response <b>&lt;socket&gt;</b>	Response <b>&lt;socket&gt;</b>
<b>OK</b>	<b>OK</b>

**Differences Description:** Supported socket types (<type>) and the starting value of created socket reference number (<socket>) in the response are different.

- **BC95**
  - 1) Only <type>=DGRAM (indicates UDP socket) is supported.
  - 2) <socket>, indicating a reference to created socket, supports values starting from 0 or 1.
- **BC95-G**
  - 1) Both <type>=DGRAM (indicates UDP socket) and <type>=STREAM (indicates TCP socket) are supported.
  - 2) <socket>, indicating a reference to created socket, supports values starting from 1, 2 or 3.
  - 3) Additional parameters <af\_type> and <ip address> are supported.

#### 3.3.2.2. AT+NSOST SendTo Command (UDP Only)

BC95	BC95-G
Write Command <b>AT+NSOST=&lt;socket&gt;,&lt;remote_addr&gt;,&lt;remote _port&gt;,&lt;length&gt;,&lt;data&gt;</b>	Write Command <b>AT+NSOST=&lt;socket&gt;,&lt;remote_addr&gt;,&lt;remote _port&gt;,&lt;length&gt;,&lt;data&gt;[,&lt;sequence&gt;]</b>
Response <b>&lt;socket&gt;,&lt;length&gt;</b>	Response <b>&lt;socket&gt;,&lt;length&gt;</b>
<b>OK</b>	<b>OK</b>

**Differences Description:** The maximum data length and the return values are different.

- **BC95**
  - 1) Supports data transmission of maximally 512 bytes at a time with **<length>** and **<data>**.
  - 2) The return value does not support URC reporting.
- **BC95-G**
  - 1) Supports data transmission of maximally 1358 bytes at a time with **<length>** and **<data>**.
  - 2) Parameter **<sequence>** is additionally supported. After the transmission is completed, if **<sequence>** is set from 1 to 255, the result will be reported as URC in the form of **+NSOSTR:<socket>,<sequence>,<status>**.

### 3.3.2.3. AT+NSOSTF SendTo Command with Flags (UDP Only)

BC95	BC95-G
Write Command <b>AT+NSOSTF=&lt;socket&gt;,&lt;remote_addr&gt;,&lt;remote_port&gt;,&lt;flag&gt;,&lt;length&gt;,&lt;data&gt;</b>	Write Command <b>AT+NSOSTF=&lt;socket&gt;,&lt;remote_addr&gt;,&lt;remote_port&gt;,&lt;flag&gt;,&lt;length&gt;,&lt;data&gt;[,&lt;sequence&gt;]</b>
Response <b>&lt;socket&gt;,&lt;length&gt;</b>	Response <b>&lt;socket&gt;,&lt;length&gt;</b>
OK	OK

**Differences Description:** The maximum data length and the return values are different.

- **BC95**
  - 1) Supports data transmission of maximally 512 bytes at a time with **<length>** and **<data>**.
  - 2) The return value does not support URC reporting.
- **BC95-G**
  - 1) Supports data transmission of maximally 1358 bytes at a time with **<length>** and **<data>**.
  - 2) Parameter **<sequence>** is additionally supported. After the transmission is completed, if **<sequence>** is set from 1 to 255, the result will be reported as URC in the form of **+NSOSTR:<socket>,<sequence>,<status>**.

### 3.3.3. UART Baud Rate Configuration Related Command

#### 3.3.3.1. AT+NATSPEED Configure UART Port Baud Rate

BC95	BC95-G
Test Command	Test Command

AT+NATSPEED=?	AT+NATSPEED=?
Response <b>+NATSPEED:(4800,9600,57600,115200),(0-30), (0,1),(0-3),(1,2)</b>	Response <b>+NATSPEED:(4800,9600,57600,115200,230400,460800),(0-30),(0,1),(0-3),(1,2),(0-2),(0,1)</b>
OK	OK

**Differences Description:** Default return values are different.

- **BC95**  
Only supports 4 baud rates.
- **BC95-G**  
Supports 6 baud rates, as well as parity check and software flow control.

### 3.3.4. Huawei IoT Platform Related Commands

#### 3.3.4.1. AT+NMGS Send a Message

BC95	BC95-G
Write Command <b>AT+NMGS=&lt;length&gt;,&lt;data&gt;</b>	Write Command <b>AT+NMGS=&lt;length&gt;,&lt;data&gt;[,&lt;seq_num&gt;]</b>
Response <b>OK</b>	Response <b>OK</b>
<b>[+NSMI:&lt;status&gt;]</b>	<b>[+NSMI:&lt;status&gt;[,&lt;seq_num&gt;]]</b>

**Differences Description:** Parameters supported by the command are different.

- **BC95**
  - 1) Does not support **<seq\_num>**.
  - 2) When sent message status indication is enabled with **AT+NSMI=1**, the URC in the form of **+NSMI:<status>** will be reported and the parameter **<status>** indicates SENT or DISCARDED.
- **BC95-G**
  - 1) Supports **<seq\_num>**, of which the range is 1-255.
  - 2) When sent message status indication is enabled with **AT+NSMI=1**, the URC in the form of **+NSMI:<status>[,<seq\_num>]** will be reported and the parameter **<status>** indicates SENT, SENT\_TO\_AIR\_INTERFACE or DISCARDED.



**NOTE**

**+NSMI:<status>** for BC95 and **+NSMI:<status>[,<seq\_num>]** for BC95-G are message status indications that will be reported after setting **AT+NSMI=1**. When **AT+NSMI=0** is set, there will only be a response of **OK** for **AT+NMGS** write command.

### 3.3.4.2. AT+NNMI New Message Indications

BC95	BC95-G
Read Command <b>AT+NNMI?</b>	Read Command <b>AT+NNMI?</b>
Response <b>+NNMI:0</b>	Response <b>+NNMI:1</b>
<b>OK</b>	<b>OK</b>

**Differences Description:** Default return values are different:

- **BC95**  
The default return value is 0.
- **BC95-G**  
The default return value is 1.

### 3.3.4.3. AT+QLWULDATAEX Send CON/NON Message

BC95	BC95-G
Write Command <b>AT+QLWULDATAEX=&lt;length&gt;,&lt;data&gt;,&lt;mode&gt;</b>	Write Command <b>AT+QLWULDATAEX=&lt;length&gt;,&lt;data&gt;,&lt;mode&gt;[,&lt;seq_num&gt;]</b>
Response <b>OK</b>	Response <b>OK</b>
<b>[+QLWULDATASTATUS:&lt;status&gt;]</b>	<b>[+QLWULDATASTATUS:&lt;status&gt;[,&lt;seq_num&gt;]]</b>

**Differences Description:** Parameters supported by the command are different.

- **BC95**  
1) Does not support **<seq\_num>**.

- 2) The URC in the form of **+QLWULDATASTATUS:<status>** will be reported when it is configured to send a CON message (<mode> is set to 0x0100).

- **BC95-G**

- 1) Supports <seq\_num>, of which the range is 0-255.
- 2) The URC in the form of **+QLWULDATASTATUS:<status>[,<seq\_num>]** will be reported when it is configured to send a CON message (<mode> is set to 0x0100).

#### 3.3.4.4. AT+QLWULDATASTATUS Query CON Messages Sent Status

BC95	BC95-G
Read Command <b>AT+QLWULDATASTATUS?</b>	Read Command <b>AT+QLWULDATASTATUS?</b>
Response <b>+QLWULDATASTATUS:&lt;status&gt;</b>	Response <b>+QLWULDATASTATUS:&lt;status&gt;[,&lt;seq_num&gt;]</b>
<b>OK</b>	<b>OK</b>

**Differences Description:** Parameters returned by the command are different.

- **BC95**

Only <status> will be returned.

- **BC95-G**

<status> and <seq\_num> will be returned.

#### 3.3.4.5. AT+NMSTATUS Message Registration Status

BC95	BC95-G
Test Command <b>AT+NMSTATUS=?</b>	Test Command <b>AT+NMSTATUS=?</b>
Response <b>UNINITIALISED</b>	Response <b>UNINITIALISED</b>
<b>MISSING_CONFIG</b>	<b>MISSING_CONFIG</b>
<b>INIT_FAILED</b>	<b>INITIALISING</b>
<b>INITIALISING</b>	<b>INITIALISED</b>

INITIALISED	INIT_FAILED
REGISTERING	REGISTERING
REREGISTERING	REGISTERED
REGISTERED	DEREGISTERED
REREGISTERED	MO_DATA_ENABLED
MO_DATA_ENABLED	NO_UE_IP
NO_UE_IP	REJECTED_BY_SERVER
MEMORY_ERROR	TIMEOUT_AND_RETRYING
COAP_ERROR	REG_FAILED
MSG_SEND_FAILED	DEREG_FAILED
REJECTED_BY_SERVER	OK
TIMEOUT_AND_RETRYING	
TIMEOUT_AND_FAILED	
OK	

**Differences Description:** Default return values of the command are different:

- **BC95**  
17 types of message registration status are supported.
- **BC95-G**  
14 types of message registration status are supported.

#### 3.3.4.6. AT+QSECSWT Set Data Encryption Mode

BC95	BC95-G
Write Command <b>AT+QSECSWT=&lt;type&gt;[,&lt;renegotiation time&gt;]</b>	Write Command <b>AT+QSECSWT=&lt;type&gt;[,&lt;NAT type&gt;]</b>

Response  
OK

Response  
OK

**Differences Description:** Setting parameters of the command are different.

- **BC95**  
Supports setting parameter **<renegotiation time>** to configure the renegotiation time.
- **BC95-G**  
Supports fixed renegotiation times based on different **<NAT type>** types.

### 3.3.5. Other Commands

#### 3.3.5.1. AT+NPING Test IP Network Connectivity to a Remote Host

BC95	BC95-G
Write Command <b>AT+NPING=&lt;remote_address&gt;[,&lt;p_size&gt;[,&lt;timeout&gt;]]</b>	Write Command <b>AT+NPING=&lt;remote_address&gt;[,&lt;p_size&gt;[,&lt;timeout&gt;]]</b>
Response OK	Response OK

**Differences Description:** The value range of **<p\_size>** (indicating the size in bytes of echo packet payload) is different.

- **BC95**  
Supports a range from 8 to 1460 for **<p\_size>**, and the default value is 8.
- **BC95-G**  
Supports a range from 12 to 1500 for **<p\_size>**, and the default value is 12.

#### 3.3.5.2. AT+CGDCONT Define a PDP Context

BC95	BC95-G
Test Command <b>AT+CGDCONT=?</b>	Test Command <b>AT+CGDCONT=?</b>
Response <b>+CGDCONT:(0-10),("IP","NONIP"),,,(0),(0),,,,(0,1)</b>	Response <b>+CGDCONT:(0-10),("IP","NONIP","IPV6","IPV4V6"),,,(0),(0),,,,(0,1)</b>

<b>OK</b>	<b>OK</b>
Write Command <b>AT+CGDCONT=&lt;cid&gt;[,&lt;PDP_type&gt;[,&lt;APN&gt;]]</b>	Write Command <b>AT+CGDCONT=&lt;cid&gt;[,&lt;PDP_type&gt;[,&lt;APN&gt;[,,,,,,&lt;NSLPI&gt;]]]</b>
Response <b>OK</b>	Response <b>OK</b>

**Differences Description:** <APN> values and PDP types (<PDP\_type>) are different.

- **BC95**
  - 1) <APN> value will be acquired even when not being configured.
  - 2) The default <PDP\_type> is IPv4.
- **BC95-G**
  - 1) <APN> value, which is empty when not being configured, is set by the write command.
  - 2) The default <PDP\_type> is IPv4v6.

### 3.3.5.3. AT+NCONFIG Configure UE Behaviors

BC95	BC95-G
Read Command <b>AT+NCONFIG?</b>	Read Command <b>AT+NCONFIG?</b>
Response <b>+NCONFIG:AUTOCONNECT,TRUE</b> <b>+NCONFIG:CR_0354_0338_SCRAMBLING,TRUE</b> <b>+NCONFIG:CR_0859_SI_AVOID,TRUE</b> <b>+NCONFIG:COMBINE_ATTACH,FALSE</b> <b>+NCONFIG:CELL_RESELECTION,FALSE</b> <b>+NCONFIG:ENABLE_BIP,FALSE</b>  <b>OK</b>	Response <b>+NCONFIG:AUTOCONNECT,TRUE</b> <b>+NCONFIG:CR_0354_0338_SCRAMBLING,TRUE</b> <b>+NCONFIG:CR_0859_SI_AVOID,TRUE</b> <b>+NCONFIG:COMBINE_ATTACH,FALSE</b> <b>+NCONFIG:CELL_RESELECTION,TRUE</b> <b>+NCONFIG:ENABLE_BIP,FALSE</b> <b>+NCONFIG:MULTITONE,TRUE</b> <b>+NCONFIG:NAS_SIM_POWER_SAVING_ENABLE,TRUE</b> <b>+NCONFIG:BARRING_RELEASE_DELAY,64</b> <b>+NCONFIG:RELEASE_VERSION,13</b> <b>+NCONFIG:RPM,FALSE</b> <b>+NCONFIG:SYNC_TIME_PERIOD,0</b> <b>+NCONFIG:IPV6_GET_PREFIX_TIME,15</b> <b>+NCONFIG:NB_CATEGORY,1</b> <b>+NCONFIG:RAI,FALSE</b> <b>+NCONFIG:HEAD_COMPRESS,FALSE</b> <b>+NCONFIG:RLF_UPDATE,FALSE</b> <b>+NCONFIG:CONNECTION_REESTABLISHMENT,FALSE</b>  <b>OK</b>

**Differences Description:** Default return values of the command are different.

- **BC95**  
6 UE behaviors are supported.
- **BC95-G**  
18 UE behaviors are supported.

#### 3.3.5.4. AT+NUESTATS Query UE Statistics

BC95	BC95-G
Execution Command <b>AT+NUESTATS</b>	Execution Command <b>AT+NUESTATS</b>
Response <b>Signal power:-32768</b> <b>Total power:-32768</b> <b>TX power:-32768</b> <b>TX time:0</b> <b>RX time:0</b> <b>Cell ID:4294967295</b> <b>ECL:255</b> <b>SNR:-32768</b> <b>EARFCN:4294967295</b> <b>PCI:65535</b> <b>RSRQ:-32768</b>	Response <b>Signal power:-32768</b> <b>Total power:-32768</b> <b>TX power:-32768</b> <b>TX time:0</b> <b>RX time:0</b> <b>Cell ID:4294967295</b> <b>ECL:255</b> <b>SNR:-32768</b> <b>EARFCN:4294967295</b> <b>PCI:65535</b> <b>RSRQ:-32768</b> <b>OPERATOR MODE:0</b>
<b>OK</b>	<b>OK</b>

**Differences Description:** Default return values of the command are different.

- **BC95**  
OPERATOR MODE is not supported.
- **BC95-G**  
OPERATOR MODE is supported.

### 3.3.5.5. AT+NUESTATS=RADIO Query UE Statistics

BC95	BC95(R2.0)/BC95-G
Write Command <b>AT+NUESTATS=RAIOD</b>	Write Command <b>AT+NUESTATS=RAIOD</b>
Response <b>NUESTATS:RADIO,Signal power:-32768</b>	Response <b>NUESTATS:RADIO,Signal power:-32768</b>
<b>NUESTATS:RADIO,Total power:-32768</b>	<b>NUESTATS:RADIO,Total power:-32768</b>
<b>NUESTATS:RADIO,TX power:-32768</b>	<b>NUESTATS:RADIO,TX power:-32768</b>
<b>NUESTATS:RADIO,TX time:0</b>	<b>NUESTATS:RADIO,TX time:0</b>
<b>NUESTATS:RADIO,RX time:0</b>	<b>NUESTATS:RADIO,RX time:0</b>
<b>NUESTATS:RADIO,Cell ID:4294967295</b>	<b>NUESTATS:RADIO,Cell ID:4294967295</b>
<b>NUESTATS:RADIO,ECL:255</b>	<b>NUESTATS:RADIO,ECL:255</b>
<b>NUESTATS:RADIO,SNR:-32768</b>	<b>NUESTATS:RADIO,SNR:-32768</b>
<b>NUESTATS:RADIO,EARFCN:4294967295</b>	<b>NUESTATS:RADIO,EARFCN:4294967295</b>
<b>NUESTATS:RADIO,PCI:65535</b>	<b>NUESTATS:RADIO,PCI:65535</b>
<b>NUESTATS:RADIO,RSRQ:-32768</b>	<b>NUESTATS:RADIO,RSRQ:-32768</b>
<b>OK</b>	<b>NUESTATS:RADIO,OPERATOR MODE:0</b>
	<b>OK</b>

**Differences Description:** Default return values of the command are different.

- **BC95**  
OPERATOR MODE is not supported.
- **BC95-G**  
OPERATOR MODE is supported.

### 3.3.5.6. AT+NPOWERCLASS Set the Mapping for Band and Power Class

BC95	BC95-G
Test Command <b>AT+NPOWERCLASS=?</b>	Test Command <b>AT+NPOWERCLASS=?</b>
Response <b>+NPOWERCLASS:(5),(3,5)</b>	Response <b>+NPOWERCLASS:(5,8,3,28,20,1),(3,5,6)</b>
<b>OK</b>	<b>OK</b>

**Differences Description:** Supported bands and the power class value (<power class>) of the command is different.

- **BC95**  
Single band (5) is supported. And <power class> supports 3 and 5.
- **BC95-G**  
Multiple bands (5, 8, 3, 28, 20, 1) are supported. And <power class> supports 3, 5 and 6.

## 3.4. Additional AT Commands of BC95-G

The following table lists the additional AT commands of BC95-G when comparing it with BC95.

**Table 1: Additional AT Commands of BC95-G**

No.	AT Commands	Description
1	AT+QLEDMODE	Set NETLIGHT LED Function Mode
2	AT+CGCONTRDP	Read PDP Context Dynamic Parameters
3	AT+CNMPD	No More PS Data
4	AT+NQSOS	Query the List of Pending Socket Message
5	AT+NSOCO	Connect Command (TCP Only)
6	AT+NSOSD	Send Command (TCP Only)
7	+NSOCLI	Socket Close Indicator (Response Only)



8	AT+NIPINFO	IP Address Information Report
9	AT+NCPDPR	Configure PDP Context Dynamic Parameters to be Read
10	AT+NQPODCP	Query Pending Originating Data List via the Control Plane
11	AT+QDNS	Trigger DNS Domain Name Resolution
12	AT+QLWSREGIND	Register Control
13	AT+QLWULDATA	Send Data
14	AT+QLWFOTAIND	Set DFOTA Update Mode
15	AT+QREGSWT	Set Registration Mode
16	+QLWEVTIND	LwM2M Event Report (Response Only)
17	AT+QRESETDTLS	Reset DTLS Mode
18	AT+QDTLSSTAT	Query the State of DTLS
19	AT+QLWSERVERIP	Set/Delete Bootstrap/LwM2M Server IP
20	AT+QCHIPINFO	Read System Information
21	AT+NSONMI	Control UDP/TCP Downlink Data Format

**NOTE**

For more details of the above-mentioned AT commands, please refer to *Quectel\_BC95-G&BC68\_AT\_Commands\_Manual*.

# 4 Appendix A References

**Table 7: Related Documents**

SN	Document Name	Remark
[1]	Quectel_BC95_Hardware_Design	BC95 hardware design
[2]	Quectel_BC95-G_Hardware_Design	BC95-G hardware design
[3]	Quectel_BC95_AT_Commands_Manual	BC95 AT commands manual
[4]	Quectel_BC95-G&BC68_AT_Commands_Manual	BC95-G&BC68 AT commands manual

**Table 8: Terms and Abbreviations**

Abbreviation	Description
DNS	Domain Name System
DTLS	Datagram Transport Layer Security
ECID	Enhanced Cell ID
IPv4	Internet Protocol Version 4
IPv6	Internet Protocol Version 6
LwM2M	Lightweight Machine to Machine
NB-IoT	Narrow Band Internet of Thing
OTDOA	Observed Time Difference of Arrival
PDP	Packet Data Protocol
PLMN	Public Land Mobile Network
TCP	Transmission Control Protocol
UART	Universal Asynchronous Receiver/Transmitter

---

UE	User Equipment
UDP	User Datagram Protocol
URC	Unsolicited Result Code

---