



## Single-deck terminal block - Stackable version - Pitch 7mm - 2÷6 poles

### GENERAL INFORMATION

pitch:	7 mm
housing height:	12,60 mm
housing depth:	8.2 mm
dimensional class:	slow
wire section:	1.5 mm <sup>2</sup> / 16 AWG
clamp opening size:	1.8 x 2.6 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +130°C

### ELECTRICAL CHARACTERISTICS

current:	13,5A
voltage:	450V
test voltage:	2.5 kVrms/60s

### MECHANICAL CHARACTERISTICS

screw:	M2
max. torque:	0.2 Nm / 1.8 in.lbs

### APPROVALS DATA



EN 60998-1

current:	17.5A
voltage:	450V
wire section:	1.5mm <sup>2</sup>
torque:	0.2Nm
FILE:	CA02.04718



-  
-  
-  
-  
-



UL 1059
12A factory / 10A field
300V
16÷30AWG
1.8Lb-in
E178356

**MATERIALS**

housing: PA - UL 94 V0  
 screw: Galvanized steel  
 clamp/spring: Tin-plated copper alloy  
 terminal: Tin-plated copper alloy

**AVAILABLE COLOURS**

other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MVS132-7-V-L	N/A	N/A	N/A
3	MVS133-7-V-L	N/A	N/A	N/A
4	MVS134-7-V-L	N/A	N/A	N/A
5	MVS135-7-V-L	N/A	N/A	N/A
6	MVS136-7-V-L	N/A	N/A	N/A