
Item no.: 2003-7645
Product description: MULTILEVEL INSTALLATION TERMINAL BLOCK L/L/PE



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Product group	22 (TOPJOB S RAIL-MOUNTED TERMINAL BLOCKS)
Number of levels	3
Cross section [mm ²]	0.25 - 2.5 mm ²
Cross section [AWG]	22 - 12 AWG
Connection method	CAGE CLAMP®S Connection
Cross section [mm ²]	0.25 - 4 mm ²
Cross section [AWG]	22 - 12 AWG
Wiring method	e+f
Connection method	CAGE CLAMP®S Connection
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Weight	16.388 g
Color	gray
Wiring type	Front-entry
No. of connection Points	5
No. of potentials	3
Height	42.5 mm

Height
Width
Width

1.673 in
5.2 mm
0.205 in



Depth	96 mm
Depth	3.78 in
Strip length from	10 mm
Strip length to	12 mm
Strip length	0.43 in
Customs Tariff No.	85369010
Country of Origin	Deutschland
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
2003-7645	CCA	NL6341	250/400	32	0,25-4
2003-7645	KEMA	NL2079570.51	250/400	32	0,25-4

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected