



E3AS-L200MT M3

Photoelectric sensor, rectangular housing, stainless steel, red LED, background suppression, 200 mm, PNP, Light-ON/Dark-ON, IO-Link COM3, M8 4-pin connector

Specifications

Shape	Cuboid
Sensing method	Background suppression
Sensing distance	200 mm
Sensing distance (min.)	10 mm
Setting method	IO-Link, Teach-In
Connection method	Connector M8 - 4 pin
Output type	IO-Link, PNP
Operation mode	Dark-ON, Light-ON
IO-Link baud rate	COM3 (230.4 kbps)
Response time	1 ms
Material housing	Stainless steel
Product Width (unpacked)	11.4 mm
Product Height (unpacked)	38 mm
Product Depth (unpacked)	22 mm
Type of light	Polarity free red light
Spot size	25 x 25 mm
Power supply voltage	10-30 V

Accessories



E39-L211

Mounting bracket for E3AS sensor, L shaped



E39-L212

Protective mounting bracket for E3AS, vertical mounting



E39-L214

Protective metal cover for E3AS, horizontal surface mounting

Related products



M8 Connectors & Cordsets

Industrial connectors & cordsets for any application

CAD Library



E3AS – Automotive Brochure

EN PDF 18.7 MB



E3AS – Food & Commodities Datasheet

EN PDF 18.1 MB



E3AS-L Index list

EN PDF 1.36 MB



E3AS-L Instruction Sheet

EN PDF 312 KB



E3AS-Lxx[x]xx IO-Link IODD file

EN ZIP 567 KB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



IO-Link Series Brochure

EN PDF 8.05 MB