



Pushing Performance
Since 1945

MPP ix Type B 10xAWG26 Signal PUR 10m



Image is for illustration purposes only. Please refer to product description.

Part number	33 48 353 5A21 100
Specification	MPP ix Type B 10xAWG26 Signal PUR 10m
HARTING eCatalogue	https://harting.com/33483535A21100

Identification

Category	System cabling
Series	HARTING Mini PushPull
Identification	HARTING ix Industrial®
Element	Cable assemblies
Specification	Pre-assembled on both sides
Connector 1	HARTING Mini PushPull
	HARTING ix Industrial® Type B
	Overmoulded
Connector 2	HARTING Mini PushPull
	HARTING ix Industrial® Type B
	Overmoulded
Type of cable	Copper cable (round)

Version

Cable length	10 m
Number of cores	10
Core structure	10x AWG 26
Termination method	IDC insulation displacement termination

Technical characteristics

Limiting temperature	-40 ... +70 °C
Degree of protection acc. to IEC 60529	IP65
	IP67



Pushing Performance
 Since 1945

Material properties

Material (cable)	PUR (polyurethane)
Colour (cable)	Grey
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 61076-3-124
----------------	-----------------

Commercial data

Packaging size	1
Country of origin	Latvia
European customs tariff number	85444290
GTIN	5713140260917
eCl@ss	27060390 Ready-made data cable (unspecified)
ETIM	EC002599
UNSPSC 24.0	26121600