



FEATURES:
MATERIAL : PBT UL94V-0

SPECIFICATION:
PITCH BETWEEN POLES : 2.54mm
CURRENT RATING : 3A
VOLTAGE RATING : 250V AC/DC
CONTACT RESISTANCE : INITIAL VALUE/10mΩ max.
AFTER ENVIRONMENTAL TESTING/20mΩ max.
INSULATION RESISTANCE : 1000MΩ (min.)
WITHSTAND VOLTAGE : 1000V AC/MINUTE
TEMPERATURE RANGE : -25°C TO +85°C
APPLCABLE WIRE : AWG #22 TO #28

741-7 5 -2xx B 03
1 2 3 4

1. 7: Green Product
2. 2xx: 2*xxPin Dual rows
3. B: Black Insulator
4. Pinrex internal code.

Dimensional and Order information

Circuits	Dimensions mm		Circuits	Dimensions mm	
	A	B		A	B
04	2.54	5.08	42	50.80	53.34
06	5.08	7.62	44	53.34	55.88
08	7.62	10.16	46	55.88	58.42
10	10.16	12.70	48	58.42	60.96
12	12.70	15.24	50	60.96	63.50
14	15.24	17.78	52	63.50	66.04
16	17.78	20.32	54	66.04	66.58
18	20.32	22.86	56	66.58	71.72
20	22.86	25.40	58	71.72	73.66
22	25.40	27.94	60	73.66	76.20
24	27.94	30.48	62	76.20	78.74
26	30.48	33.02	64	78.74	81.28
28	33.02	35.56	66	81.28	83.82
30	35.56	38.10	68	83.82	86.36
32	38.10	40.64	70	86.36	88.90
34	40.64	43.18	72	88.90	91.44
36	43.18	45.72	74	91.44	93.98
38	45.72	48.26	76	93.98	96.52
40	48.26	50.80	78	96.52	99.06
			80	99.06	101.60



		TOLERANCE		UNITS : mm		OLD PART NO.		Wire To Board Housing 2.54mm Dual rows PBT		频锐科技股份有限公司 PINREX TECHNOLOGY CORP.	
		.0 =±.25 .00 =±.15 .000 =±.08 .0000=±. ANG.=±3'		SCALE NONE SIZE A4		DRAWER 罗尚雷 CHECK 李剑					
A	RELEASE	2023/03/13		SHEET 1 OF 1		REV. A		APP'D 李剑		NEW PART NO. 741-75-2xxB03	
REV.	DESCRIPTION	DATE		SCALE NONE SIZE A4		SHEET 1 OF 1		APP'D 李剑		DRAW NO. 741-75-2xxB03	